

Color Variants

RC242203

With fresh cooling close to 0 °C Fully integrated

Included accessories

2 x egg trav.

1 x wine and champagne rack.

RC242203

Refrigerator 200 series

With fresh cooling close to 0 °C

Fully integrated

Niche width 56 cm, Niche height 140

2 climate zones incl. fresh cooling close to 0 °C

Height adjustable safety glass shelves Door racks with aluminium profiles Cushioned door closing system allowing a soft and controlled door closure

Net volume 222 litres

Handling

Electronic temperature control with digital display. Touch keys.

Technical Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation.

Cushioned door closing system from 20° door opening angle, integrated in door hinge.

Open-door and malfunction alarm.

Cooling

Temperature adjustable from +3 °C to +8 °C.

4 safety glass shelves, of which 1 is fully extendable and 4 height adjustable.

1 integrated shelf.

Wine and champagne rack for 4 bottles, can be completely folded away. 1 large door rack with aluminium profile for bottles with flexible bottle holder.

3 door racks with aluminium profile. Bright interior lighting with integrated glare-free side light elements. Net volume 163 litres.

Fresh cooling close to 0 $^{\circ}\text{C}$

1 full width fresh cooling drawer close to 0 °C

Humidity can be adjusted manually. Ideal for fruit and vegetables. Ideal for meat, fish and poultry. Net volume 59 litres.

Consumption data

Energy efficiency class A++ at a range of energy efficiency classes from A++ + to D.

Energy consumption 124 kWh/year. Noise level 37 dB (re 1 pW).

Planning notes

Flat hinge. Door hinge right, reversible. Door opening angle of 115°, fixable at

Max. door panel weight 14 kg.

Connection

Total connected load 0.090 KW. Connecting cable 2.3 m with plug.

Characteristics

Built-in / Free-standing

Built-in

Number of compressors

Number of independent cooling systems

Width of the appliance

Height (mm)

1397

Depth of the product

545

Net weight (kg)

52.182

Required niche size for installation (HxWxD)

1400 x 560 x 550

Door panel options

Not possible

Door hinge

Right reversible

Number of Adjustable Shelves in fridge compartment

Shelves for Bottles

Frost free system

No

Interior ventilator No

Reversible Door Hinge

Length electrical supply cord (cm)

Noise level (dB(A) re 1 pW)

37

Multi-Flow Air Tower No

Economy setting

No

Cold technology

1 compressor/2 cold circuits

Fast cooling switch

Temperature Controlled Drawer

Humidity Control Drawer

Number of Door Bins - Refrigerator

Door bin adjustability - Refrigerator

Tilt-out door bins in fridge

Gallon Storage

Number of Gallon storage

No. of shelves in fridge

Motorized Shelf

Material of the shelves Glas, plastic

Type of Light

Door opened indicator freezer

Connection Rating (W)

Current (A)

Voltage (V)

220-240

Frequency (Hz)

Energy consumption (kWh)

Freezing capacity (kg)

Storage Period in Event of Power Failure (h)

Approval certificates

Universal Product Code

Main colour of product

N/A

Door panel options

Not possible

Installation typology Full-integrated

Noise level (dB(A) re 1 pW)

GAGGENAU

RC242203
Refrigerator 200 series
With fresh cooling close to 0 ° C
Fully integrated
Niche width 56 cm, Niche height 140 cm

2021-06-19 Page 2





