



#### Color Variants

VL041115  
Stainless steel control panel  
Width 8.5 cm

#### Installation Accessories

AD724041  
Connection piece for cylindrical duct  
DN 125  
VV200014

VL041115  
Vario downdraft ventilation 200 series  
Stainless steel control panel  
Width 8.5 cm  
Control unit  
Air extraction/air recirculation with  
remote fan unit AR 403/413 121

Ventilation element integrated in the  
worktop  
Highly efficient ventilation system at  
the cooktop  
Minimal planning and easy  
installation for air recirculation

#### Output

Maximum air output in combination  
with remote fan units s. table remote  
fan units on page xxx.

#### Features

Output control, knob operation.  
4 output levels.  
Ventilation grille, washable.  
Metal grease filter with grease drip tray,  
dishwasher-safe.  
No duct connecting piece included.

#### Consumption data

Consumption data is referred to a  
configuration with the remote fan unit  
AR 403 121.  
Energy efficiency class B at a range of  
energy efficiency classes from A++ to  
E.  
Energy consumption 70 kWh/year.  
Ventilation efficiency class B.  
Illumination efficiency class -.  
Grease filter efficiency class D.  
Sound level min. 52 dB / max. 67 dB  
normal mode.

#### Planning notes

No additional switch necessary.  
Air extraction in combination with  
remote fan unit AR 403 121 or air  
recirculation mode with AR 413 121.  
Please refer to page xxx for  
recommended configurations of  
downdraft ventilations and remote fan  
units and the needed ducting elements.  
Maximum cooktop width between 2 VL:  
60 cm (exception: VI/VE 270).  
If installed next to gas appliances,  
the ventilation moulding LS 041 001  
is recommended to ensure maximum  
performance of the cooktop. If installed  
next to gas appliances, flat ducts must  
not be used for the piping up to the fan  
unit.  
When having installed the ventilation  
moulding LS 041 001 the wok pan WP  
400 001 can not be used.  
When installing a ventilation hood with  
air extraction mode and a chimney-  
vented fireplace, the hood's power  
supply line needs a suitable safety  
switch.  
Please read additional planning notes  
on page xx.

#### Connection

Connecting cable 1.5 m with plug.

#### Characteristics

Product name/family  
Color chimney  
Typology  
Approval certificates  
Australia Standards, CE, Eurasian, G-  
Mark, Ukraine, VDE  
Length electrical supply cord (cm)  
150  
Required niche size for installation  
(HxWxD)  
320mm x 78.0mm x 490mm  
Height of the chimney (mm)  
Height of product, without chimney  
(mm)  
Net weight (kg)  
2.535  
Type of control  
mechanical  
Number of speed settings  
4  
Maximum output air extraction (m3/h)  
440  
Boost position output recirculating  
(m3/h)  
Maximum output recirculating air (m3/  
h)  
Boost position air extraction (m³/h)  
Number of lights  
Noise level (dB(A) re 1 pW)  
67  
Diameter of air outlet (mm)  
150  
Grease filter material  
Washable aluminium  
Odour filter  
No  
Operating Mode  
Convertible  
Delay Shut off modes  
Required accessories  
Optional accessories  
Type of lamps used  
Total power of the lamps (W)  
Grease filter type  
Multilayer  
Clean filter reminders

Consumption and connection features  
Connection Rating (W)  
Current (A)  
10  
Voltage (V)  
220-240  
Frequency (Hz)  
50  
Plug type  
Installation typology  
Built-in  
Universal Product Code  
825225916192  
Material body  
Stainless steel  
Approval certificates  
Australia Standards, CE, Eurasian, G-  
Mark, Ukraine, VDE  
Length of electrical supply cord (in)  
Plug type  
Dimensions of the product, with  
chimney (if exists) (in)  
/ x x  
Dimensions of the packed product (in)  
7.24 x 11.41 x 23.42  
Height of the chimney (in)  
Vertical rise height  
Required distance above cooktop/  
ranges  
Net weight (lbs)  
6  
Gross weight (lbs)  
12  
Motor location  
N/A  
Maximum output recirculating air (CFM)  
Diameter of air duct (in) top  
Diameter of air duct (in) back  
Discharge direction  
No-return airflow flap  
No  
Length electrical supply cord (cm)