



AC231120
Ceiling ventilation 200 series
Stainless steel and glass
Width 120 cm
Air recirculation

Easy and time saving installation directly in the ceiling
Rim extraction with flat and easy-to-clean glass underside
Dimmable, indirect LED light
Air recirculation

Output

Performance and noise level, output level 3/Intensive:
Air output according to EN 61591.
Sound power level according to EN 60704-3.
Sound pressure level according to EN 60704-2-13.
Odour reduction for air recirculation in accordance with EN 61591.
Air recirculation:
780 / 850 m³/h.
70 / 72 dB (A) re 1 pW.
56 / 58 dB (A) re 20 µPa.

Features

3 electronically controlled power levels and 1 intensive mode.
Remote control is included in delivery.
Interval ventilation, 10 min.
Run-on function, 15 min.
Grease filter saturation indicator.
Metal grease filter, dishwasher-safe.
Activated charcoal filter fitted in appliance ex factory.
Activated charcoal filter saturation indicator.
Activated charcoal filter regenerable up to four times.
Stainless steel housing and glass filter cover in Gaggenau Silver.
Indirect LED light (4000 K), dimmable.
Lamp output 2 x 6 W.
Illuminance 14 lx.
2 high-performance fans.

Consumption data

Sound level min. 57 dB / max. 70 dB normal mode.

Planning notes

Installation directly on the ceiling.
A suitable load-bearing substructure is required for securing the extractor hood. Never fit the appliance directly onto plasterboard or similar lightweight construction materials.
Note the position of the electrical outlet.
Recommended minimum gap between filter openings and wall: 50 cm.
Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).
Clearance above electric appliances min. 55 cm.
Maximum clearance above cooktops 150 cm.
The capture of vapours will be inefficient if the ceiling ventilation is positioned too high.
The cooktop should be no wider than the ceiling ventilation.
To achieve optimum vapour extraction, the ceiling ventilation must at least cover the hob. It should be positioned centrally over the hob. It cannot be combined with VR or VP.
Appliance weight: approx. 41 kg.

Connection

Total connected load 192 W.
Plan a connection cable.

Characteristics

Product name/family
Color chimney
Typology
Traditional
Approval certificates
Australia Standards, CE, G-Mark
Length electrical supply cord (cm)
0
Required niche size for installation (HxWxD)
Height of the chimney (mm)
Height of product, without chimney (mm)
Net weight (kg)
40.526
Type of control
Electronic
Number of speed settings
Maximum output air extraction (m³/h)
Boost position output recirculating (m³/h)
850
Maximum output recirculating air (m³/h)
780
Boost position air extraction (m³/h)
Number of lights
2
Noise level (dB)
70
Diameter of air outlet (mm)
150
Grease filter material
Washable aluminium
Odour filter
Yes
Operating Mode
Recirculating air only
Delay Shut off modes
15M
Required accessories
Optional accessories
AA200120
Type of lamps used
Total power of the lamps (W)
12
Grease filter type
Kassette
Clean filter reminders

Consumption and connection features
Connection Rating (W)
192
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
no plug
Installation typology
Built-in
Universal Product Code
Material body
Glass
Approval certificates
Australia Standards, CE, G-Mark
Length of electrical supply cord (in)
Plug type
no plug
Dimensions of the product, with chimney (if exists) (in)
/ x x
Dimensions of the packed product (in)
16.53 x 37.40 x 57.08
Height of the chimney (in)
Vertical rise height
Required distance above cooktop/ranges
Net weight (lbs)
89
Gross weight (lbs)
133
Motor location
Integrated motor in hood body
Maximum output recirculating air (CFM)
Diameter of air duct (in) top
Diameter of air duct (in) back

Color Variants

AC231120
Stainless steel and glass
Width 120 cm

Optional accessories

AA200120
Activated charcoal filter

AC231120
Ceiling ventilation 200 series
Stainless steel and glass
Width 120 cm
Air recirculation
2019-11-09
Page 2

