

Color Variants

BO420101

Full glass door in Gaggenau Anthracite Width 60 cm

Included accessories

1 x enamel baking trav. suit. pyrolitic clean.

1 x glass pan.

1 x grill shelf.

Optional accessories

BA016105

Pull-out system BA026115

Baking tray, enamelled

BA036105

Wire rack. chromium-plated

BA046115

Glass trav

BA056115

Heating element for baking stone and Gastronorm roaster.

BA056133 Baking stone.

BA226105

Grill tray, enamelled

BS020002

Pizza paddle, set of 2.

Gastronorm roaster in cast aluminium.

Installation Accessories

BA476110

Handle bar, stainless steel

Product Variants

BO421101 Oven 400 series

Full glass door in Gaggenau Anthracite Width 60 cm

Left-hinged

Controls at the top

BO420101 Oven 400 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Right-hinged

Controls at the top

Handleless door / automatic door opening

Pyrolytic system

9 heating methods, with baking stone function

TFT touch display Panel-free appliance with surface control module

Electronic temperature control from 50 °C to 300 °C

Net volume 76 litres

Heating methods

Hot air.

Eco hot air.

Top + bottom heat.

Top heat.

Bottom heat.

Hot air + bottom heat.

Full surface grill + circulated air.

Full surface grill.

Baking stone function.

Handling

Automatic door opening.

Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 180°

angle. Features

Baking stone socket.

Actual temperature display.

Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term

60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing.

Child lock. Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Pyrolytic system.

Gaggenau enamel.

Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 47 mm from the

furniture cavity. If the handle (optional accessory) is retrofitted, the outer edge of the

door handle extends 94 mm from the furniture cavity. Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the

appliance. When planning a corner solution, pay attention to the 90° door opening

angle. To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to

Total connected load 3.7 kW.

Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in

Integrated Cleaning system

Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm) 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

760 x 730 x 660

Control Panel Material without panel

Door Material

Glass Net weight (kg)

54.457 Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Top heat

First cavity material

Enamelled

Number of interior lights

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm) Interior Lights - cavity 1

Pull-out system

Accessory

Clock function Alarm, Off, On, timer

Included accessories

1 x enamel baking tray, suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf

Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W)

3000 Convection Element Wattages cavity 1

(W) 2100

Microwave wattage cavity 1 (W)

Drawer wattage (W)

Consumption and connection features

Energy efficiency class - NEW (2010/30/EC)

Energy consumption per cycle

conventional - NEW (2010/30/EC)

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)

Energy consumption per cycle forced air convection - NEW (2010/30/EC) 0.83

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/

Energy efficiency index (2010/30/EC)

Connection Rating (W)

3700

Current (A)

Voltage (V)

220-240

Frequency (Hz) Plug type

Connecting cable type

Universal Product Code

Color / Material Front

Alternative colors available

BO420111

Energy input Electric

Approval certificates


CE, Eurasian, G-Mark, Ukraine, VDE Length of electrical supply cord (in)

Paguirad cutout/nicha siza for


BO420101 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm Right-hinged

2019-11-15 Page 2

Controls at the top



When installed next to each other



Cross section of the top/bottom door edge gaps

