

Color Variants

BOP211101

Full glass door in Gaggenau Anthracite Width 60 cm

BOP211111

Full glass door in Gaggenau Metallic Width 60 cm

BOP211131

Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x grill shelf. 1 x grill tub.

Optional accessories

BA036102

Wire rack, chromium-plated

BA046115

Glass trav BA056115

Heating element for baking stone and

Gastronorm roaster

BA056130

Baking stone.

BA216102 Quadruple telescopic pull-out rack

BA226102

Grill tray, enamelled

BA226112

Baking tray, enamelled

BS020002

Pizza paddle, set of 2

Product Variants

BOP210101

Oven 200 series

Full glass door in Gaggenau Anthracite Width 60 cm

Right-hinged

BOP211101 Oven 200 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Left-hinged

Flush installation 9 heating methods, with baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 50 °C to 300 °C Net volume 76 litres

Heating methods

Hot air.

Eco hot air.

Top + bottom heat.

Top heat.

Bottom heat.

Hot air + bottom heat.

Full surface grill + circulated air. Full surface grill.

Baking stone function.

Handling

Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 110°

Features

Baking stone socket. Actual temperature display

Rapid heating.

Timer functions: cooking time, cooking

time end, timer, stopwatch, long-term timer.

60 W halogen light on the top. Chromium-plated side shelf supports with 4 tray levels.

Safety

Thermally insulated door with triple glazing.

Child lock Safety shut-off.

Cooled housing with temperature protection.

Gaggenau enamel.

Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture

Necessary lateral gap between appliance door and furniture panel of

min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers

next to the appliance. When planning a corner solution, pay

attention to the 110° door opening

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Connection

Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in

Integrated Cleaning system

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm) 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

Control Panel Material

without panel

Door Material

Glass

Net weight (kg)

51.121 Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot air and 1/1 bottom heating, Hot

Air-Eco, Hot air grilling, Top heat First cavity material

Enamelled

Number of interior lights

Approval certificates

Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

Interior Lights - cavity 1

Pull-out system

Clock function Alarm, Off, On, timer

Included accessories cavity 1

1 x enamel baking tray, suit. pyrolitic clean, 1 x grill shelf, 1 x grill tub

Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W)

Convection Element Wattages cavity 1 (W)

2100

Microwave wattage cavity 1 (W)

Drawer wattage (W)

Consumption and connection features Energy efficiency class - NEW (2010/30/EC)

Energy consumption per cycle conventional - NEW (2010/30/EC)

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)

Energy consumption per cycle forced air convection - NEW (2010/30/EC)

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/

Energy efficiency index (2010/30/EC)

Connection Rating (W)

3700 Current (A)

Voltage (V) 220-240

Frequency (Hz)

Plug type fixed connection, no plug

Connecting cable type

Universal Product Code 825225914419

Color / Material Front **Anthracite**

Alternative colors available BOP211111, BOP211131

Energy input

Approval certificates Australia Standards, CE, Eurasian, G- Energy efficiency class A at a range of energy efficiency classes from A+++ to

Total connected load 3.7 kW. Plan a connection cable.

BOP211101 Oven 200 series Full glass door in Gaggenau Anthracite

Width 60 cm

Left-hinged

2019-09-11 Page 2

