

Color Variants

BOP220101

Full glass door in Gaggenau Anthracite Width 60 cm

BOP220111

Full glass door in Gaggenau Metallic

Width 60 cm

BOP220131 Full glass door in Gaggenau Silver

Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean.

1 x glass pan.

1 x grill shelf.

Optional accessories

BA016105

Pull-out system

BA026115 Baking tray, enamelled

BA036105

Wire rack, chromium-plated

BA046115

Glass tray

BA056115

Heating element for baking stone and

Gastronorm roaster.

BA056133

Baking stone.

BA226105

Grill tray, enamelled

BS020002

Pizza paddle, set of 2.

GN340230

Gastronorm roaster in cast aluminium.

Product Variants

BOP221101

Oven 200 series

Full glass door in Gaggenau Anthracite Width 60 cm

Left-hinged

BOP220101 Oven 200 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Right-hinged

Flush installation Pyrolytic system 9 heating methods, with baking stone function TFT touch display

Panel-free appliance with surface control module

Electronic temperature control from 50 °C to 300 °C

Net volume 76 litres

Heating methods

Hot air.

Eco hot air.

Top + bottom heat.

Top heat.

Bottom heat.

Hot air + bottom heat.

Full surface grill + circulated air. Full surface grill.

Baking stone function.

Handling

Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 110° angle.

Features

Baking stone socket. Actual temperature display. Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.

Child lock

Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel.

Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of

min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers

next to the appliance. When planning a corner solution, pay attention to the 110° door opening

angle. For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection)

must be taken into account. To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in

Integrated Cleaning system

Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm) 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

Control Panel Material

without panel Door Material

Glass

Net weight (kg)

55.283

Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Top heat

First cavity material

Enamelled

Number of interior lights

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, Ukraine, VDE

Length electrical supply cord (cm)

Interior Lights - cavity 1

Pull-out system

Clock function Alarm, Off, On, timer

Included accessories cavity 1

1 x enamel baking tray, suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf

Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W)

Convection Element Wattages cavity 1 (W)

2100

Microwave wattage cavity 1 (W)

Drawer wattage (W)

Consumption and connection features Energy efficiency class - NEW (2010/30/EC)

Energy consumption per cycle conventional - NEW (2010/30/EC)

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)

Energy consumption per cycle forced air convection - NEW (2010/30/EC)

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/

Energy efficiency index (2010/30/EC)

Connection Rating (W)

3700 Current (A)

Voltage (V)

220-240 Frequency (Hz)

Plug type

fixed connection, no plug Connecting cable type

Universal Product Code 825225914471

Color / Material Front **Anthracite**

Alternative colors available BOP220111, BOP220131

Australia Standards, CCC, CE, China,

Energy input

Electric Approval certificates energy efficiency classes from A+++ to

Energy efficiency class A at a range of

Total connected load 3.7 kW. Plan a connection cable.

Connection

BOP220101 Oven 200 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Right-hinged

2019-09-24 Page 2

