

Color Variants

BOP240111

Full glass door in Gaggenau Metallic Width 60 cm

BOP240101

Full glass door in Gaggenau Anthracite

Width 60 cm

BOP240131 Full glass door in Gaggenau Silver

Width 60 cm

Included accessories

1 x enamel baking tray.

- suit, pyrolitic clean. 1 x glass pan.
- 1 x grill shelf.

1 x pluggable meat probe.

Optional accessories

BA016105

Pull-out system

BA026115

Baking tray, enamelled

BA036105

Wire rack, chromium-plated

BA046115 Glass tray

BA056115

Heating element for baking stone and Gastronorm roaster.

BA056133

Baking stone.

BA226105

Grill tray, enamelled

BS020002

Pizza paddle, set of 2.

Product Variants

GN340230

Gastronorm roaster in cast aluminium.

BOP241111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm Left-hinged

BOP240111 Oven 200 series

Full glass door in Gaggenau Metallic

Width 60 cm

Right-hinged

Flush installation 13 heating methods with core temperature probe and baking stone

TFT touch display

Panel-free appliance with surface control module

Electronic temperature control from 30 °C to 300 °C

Net volume 76 litres

Heating methods

Hot air.

Eco hot air.

Top + bottom heat.

Top heat.

Bottom heat.

Hot air + bottom heat.

Full surface grill + circulated air.

Full surface grill.

Compact grill.

Baking stone function.

Roaster function.

Dough proofing.

Defrosting.

Handling

Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes (incl.

core temperature probe). Information key with use indicators. Side-opening door opens up to 110°

angle. **Features**

Core temperature probe with automatic shut-off.

Baking stone socket.

Actual temperature display.

Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term

60 W halogen light on the top. Chromium-plated side shelf supports

with 4 tray levels.

Safety

Thermally insulated door with triple glazing.

Child lock.

Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Back wall and ceiling with catalytic coating.

Gaggenau enamel.

Heated catalyser to clean the oven air. Grease filter in front of hot air fan.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics

Color / Material Front

Stainless steel

Built-in / Free-standing

Built-in

Integrated Cleaning system

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm) 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

780 x 760 x 680

Control Panel Material

without panel Door Material

Glass Net weight (kg)

52.054

Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat

First cavity material

Enamelled

Number of interior lights

Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

Interior Lights - cavity 1

Pull-out system

Accessory

Clock function

Alarm, Off, On, timer

Included accessories 1 x enamel baking tray, suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe

Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W)

3000 Convection Element Wattages cavity 1 (W)

2100

Microwave wattage cavity 1 (W)

Drawer wattage (W)

Consumption and connection features

Energy efficiency class - NEW (2010/30/EC)

Energy consumption per cycle conventional - NEW (2010/30/EC)

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)

Energy consumption per cycle forced air convection - NEW (2010/30/EC)

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/ EC)

Energy efficiency index (2010/30/EC) 95.4

Connection Rating (W)

Current (A)

Voltage (V)

Frequency (Hz)

Plug type

fixed connection, no plug Connecting cable type

Universal Product Code

825225914617

Color / Material Front

Stainless steel Alternative colors available BOP240101, BOP240131

Energy input

Electric

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Energy efficiency class A at a range of energy efficiency classes from A+++ to

Total connected load 3.7 kW.

Plan a connection cable

BOP240111 Oven 200 series

Full glass door in Gaggenau Metallic

Width 60 cm

Right-hinged

2019-10-29 Page 2

