BOP240131
Oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
Right-hinged

Flush installation
13 heating methods with core temperature probe and baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Color Variants

BOP240131
Full glass door in Gaggenau Silver Width 60 cm
BOP240101
Full glass door in Gaggenau Anthracite Width 60 cm
BOP240111
Full glass door in Gaggenau Metallic Width 60 cm

Included accessories

1 x enamel baking tray.
suit. pyrolitic clean.
1 x glass pan.
1 x grill shelf.
1 x pluggable meat probe.

Optional accessories

BA016105
Pull-out system
BA026115
Baking tray, enamelled
BA036105
Wire rack, chromium-plated
BA046115
Glass tray
BA056115
Heating element for baking stone and Gastronorm roaster.
BA056133
Baking stone.
BA226105
Grill tray, enamelled
BS020002
Pizza paddle, set of 2.
GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BOP241131
Oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
Left-hinged

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top heat.
Bottom heat.
Hot air + bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Option to save individual recipes (incl. core temperature probe).
Information key with use indicators.
Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off.
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
Chromium-plated side shelf supports with 4 tray levels.

Safety

Thermally insulated door with triple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Back wall and ceiling with catalytic coating.
Gaggenau enamel.
Heated catalyser to clean the oven air.
Grease filter in front of hot air fan.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics

Color / Material Front
Aluminium
Built-in / Free-standing
Built-in
Integrated Cleaning system
No
Required niche size for installation (HxWxD)
590-590 x 560-560 x 550
Dimensions of the product (mm)
595 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
780 x 760 x 680
Control Panel Material
without panel
Door Material
Glass
Net weight (kg)
52.404
Usable volume of cavity (l)
76
Cooking method
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat
First cavity material
Enamelled
Number of interior lights
1
Approval certificates
CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
Interior Lights - cavity 1
1
Pull-out system
Accessory
Clock function
Alarm, Off, On, timer
Included accessories
1 x enamel baking tray,suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe
Bake Element Wattages cavity 1 (W)
Broil Element Wattages cavity 1 (W)
3000
Convection Element Wattages cavity 1 (W)
2100
Microwave wattage cavity 1 (W)
Drawer wattage (W)

Consumption and connection features

Energy efficiency class - NEW (2010/30/EC)
A
Energy consumption per cycle conventional - NEW (2010/30/EC)
1.25
Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)
Energy consumption per cycle forced air convection - NEW (2010/30/EC)
0.83
Energy consumption gas oven per cycle forced air convection - NEW (2010/30/EC)
Energy efficiency index (2010/30/EC)
95.4
Connection Rating (W)
3700
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50; 60
Plug type
fixed connection, no plug
Connecting cable type
Universal Product Code
825225914631
Color / Material Front
Aluminium
Alternative colors available
BOP240101, BOP240111
Energy input
Electric

For installation underneath cooktops:
Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.
Total connected load 3.7 kW.
Plan a connection cable.

BOP240131

Oven 200 series

Full glass door in Gaggenau Silver

Width 60 cm

Right-hinged

2019-10-29
Page 2