



BOP250101
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged

Flush installation
Pyrolytic system
13 heating methods with core temperature probe and baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Heating methods

Hot air.
 Eco hot air.
 Top + bottom heat.
 Top heat.
 Bottom heat.
 Hot air + bottom heat.
 Full surface grill + circulated air.
 Full surface grill.
 Compact grill.
 Baking stone function.
 Roaster function.
 Dough proofing.
 Defrosting.

Handling

Rotary knob and TFT touch display operation.
 Clear text display.
 Option to save individual recipes (incl. core temperature probe).
 Information key with use indicators.
 Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off.
 Baking stone socket.
 Actual temperature display.
 Rapid heating.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
 60 W halogen light on the top.
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
 Gaggenau enamel.
 Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
 The door panel surface of the appliance extends 21 mm from the furniture cavity.
 The outer edge of the door handle extends 72 mm from the furniture cavity.
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics

Color / Material Front
 Anthracite

Built-in / Free-standing
 Built-in

Integrated Cleaning system
 Pyrolytic

Required niche size for installation (HxWxD)
 590-590 x 560-560 x 550

Dimensions of the product (mm)
 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)
 780 x 760 x 680

Control Panel Material
 without panel

Door Material
 Glass

Net weight (kg)
 54.149

Usable volume of cavity (l)
 76

Cooking method
 Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat

First cavity material
 Enamelled

Number of interior lights
 1

Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)
 1

Interior Lights - cavity 1
 1

Pull-out system
 Accessory

Clock function
 Alarm, Off, On, timer

Included accessories
 1 x enamel baking tray, suit. pyrolytic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe

Bake Element Wattages cavity 1 (W)
 3000

Broil Element Wattages cavity 1 (W)
 3000

Convection Element Wattages cavity 1 (W)
 2100

Microwave wattage cavity 1 (W)
 2100

Drawer wattage (W)

Consumption and connection features
Energy efficiency class - NEW (2010/30/EC)
 A

Energy consumption per cycle conventional - NEW (2010/30/EC)
 1.25

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)
 0.83

Energy consumption per cycle forced air convection - NEW (2010/30/EC)
 0.83

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/EC)
 0.83

Energy efficiency index (2010/30/EC)
 95.4

Connection Rating (W)
 3700

Current (A)
 16

Voltage (V)
 220-240

Frequency (Hz)
 50

Plug type
 fixed connection, no plug

Connecting cable type
 Universal Product Code
 825225914716

Color / Material Front
 Anthracite

Alternative colors available
 BOP250111, BOP250131

Energy input

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 kW.
 Plan a connection cable.

Color Variants

BOP250101
Full glass door in Gaggenau Anthracite
Width 60 cm

BOP250111
Full glass door in Gaggenau Metallic
Width 60 cm

BOP250131
Width 60 cm
Right-hinged

Included accessories

1 x enamel baking tray.
 suit. pyrolytic clean.
 1 x glass pan.
 1 x grill shelf.
 1 x pluggable meat probe.

Optional accessories

BA016105
Pull-out system

BA026115
Baking tray, enamelled

BA036105
Wire rack, chromium-plated

BA046115
Glass tray

BA056115
Heating element for baking stone and Gastronorm roaster.

BA056133
Baking stone.

BA226105
Grill tray, enamelled

BS020002
Pizza paddle, set of 2.

GN340230
Gastronorm roaster in cast aluminium.

Product Variants

BOP251101
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Left-hinged

BOP250101
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged
2019-11-14
Page 2

