



#### Color Variants

**BX480611**  
Stainless steel-backed full glass door  
Width 76 cm

#### Optional accessories

**BA018165**  
Pull-out system

**BA028115**  
Baking tray, enamelled

**BA038165**  
Wire rack, chromium-plated.

**BA058115**  
Heating element for baking stone and  
Gastronorm roaster.

**BA058133**  
Baking stone.

**BS020002**  
Pizza paddle, set of 2.

**GN340230**  
Gastronorm roaster in cast aluminium.

**BX480611**  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Right-hinged  
Controls centered

Pyrolytic system  
17 heating methods with core temperature probe, rotisserie spit and baking stone function  
TFT touch display  
Electronic temperature control from 85 °F to 550 °F  
2x 2.8 cu. ft. net volume

#### Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

#### Handling

Rotary knob and TFT touch display operation.  
Clear text display.  
Information key with use indicators.  
Side-opening door opens up to 180° angle.

#### Features

Core temperature probe with automatic shut-off (lower oven).  
Rotisserie spit (lower oven).  
Baking stone socket.  
Actual temperature display.  
Rapid heating.  
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
60 W halogen light on the top.  
10 W halogen light on the side.  
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with quadruple glazing.  
Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
Gaggenau enamel.  
Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.  
The façade of the appliance extends 1 7/8" (47 mm) from the furniture cavity.  
The outer edge of the door handle extends 3 11/16" (94 mm) from the furniture cavity.  
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
When planning a corner solution, pay attention to the 90° door opening angle.  
To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing.  
The mains socket needs to be planned outside of the built-in niche.

#### Connection

Energy efficiency class "blank".  
Total connected load 9.2 KW.  
Total Amps: 40 A.  
208 / 220 - 240 V / 60 Hz.  
Connecting cable 70 7/8" (1.8 m) without plug.

#### Characteristics

**Color / Material Front**  
Stainless steel

**Built-in / Free-standing**  
Built-in

**Integrated Cleaning system**

**Dimensions**  
1428 x 752 x 547

**Dimensions of the packed product (HxWxD) (mm)**  
1765 x 755 x 840

**Control Panel Material**  
Alu

**Door Material**  
Glass

**Net weight (kg)**  
149.710

**Usable volume of cavity (l)**  
110

**Cooking method**  
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

**First cavity material**

**Number of interior lights**  
2

**Approval certificates**  
CSA, ETL, UL

**Length electrical supply cord (cm)**  
180.0

**Cooking method second cavity**  
Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

**Timer**  
Yes

**Included accessories cavity 1**

**Bake Element Wattages cavity 1 (W)**  
1700

**Broil Element Wattages cavity 1 (W)**  
3900

**Convection Element Wattages cavity 1 (W)**  
1900

**Microwave wattage cavity 1 (W)**

**Consumption and connection features**

**Energy efficiency rating**  
N/A

**Energy consumption per cycle conventional - NEW (2010/30/EC)**  
1.53

**Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)**

**Energy consumption per cycle forced air convection - NEW (2010/30/EC)**  
1.08

**Energy consumption gas oven per cycle forced air convection - NEW (2010/30/EC)**

**Energy efficiency index (2010/30/EC)**  
106.9

**Connection rating (W)**  
9200

**Current (A)**  
40

**Voltage (V)**  
208/220-240

**Frequency (Hz)**  
60

**Plug type**  
fixed connection

**Connecting cable type**

**Universal Product Code**  
825225911142

**Color / Material Front**  
Stainless steel

**Alternative colors available**

**Energy input**  
Electric

**Approval certificates**  
CSA, ETL, UL

**Length of electrical supply cord (in)**

# GAGGENAU

**BX480611**  
**Double oven 400 series**  
**Stainless steel-backed full glass door**  
**Width 76 cm**  
**Right-hinged**  
**Controls centered**  
**2020-11-25**  
**Page 2**

