

Color Variants

CI422101 Frameless Width 38 cm

Optional accessories

CA051300

Teppan Yaki plate made of multi ply material

CA052300

Griddle plate in cast aluminium

GP900001

Stainless steel frying sensor pan

GP900002

Stainless steel frying sensor pan

GP900003

Stainless steel frying sensor pan

Installation Accessories

VA422000

Connection strip for combination within SETs CVL410 and CVL420.

CI422101

Flex induction cooktop 400 series

Frameless

Width 38 cm

For combination within the set CVL 410

Flex function for combining the rectangular cooking areas Free positioning of cookware inside combined cooking areas Frying sensor function for temperature control in pans Easy control of all functions with bicoloured display Solid stainless steel control knob Frameless for flush mounting

Cooking zones

2 flex induction cooking areas 19x24 cm (2200 W, with booster 3700 W), linked together 38x24 cm (3300 W, with booster 3700 W).

Handling

Control knobs with illuminated ring, cooking zone and output level markings.

Electronic power control in 12 output

User friendly control with bicoloured display (white / orange).

Features

Flex function for rectangular cooking areas. Frying sensor function. Booster function.

Stopwatch.

Short-term timer. Options menu.

Individual residual heat indicators. Safety shut-off.

Planning notes

For combination within the sets CVL 410 / 420.

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Appliance weight: approx. 10 kg.

Connection

Total connected load 3.7 KW. Connecting cable 1.5 m without plug.

Characteristics

Product name/family

Vario/Domino cooking zone cera

Built-in / Free-standing

Built-in

Energy input

Electric

Total number of positions that can be used at the same time

Required niche size for installation (HxWxD)

56 x 360-389 x 492-527

Width of the appliance

Dimensions

56 x 383 x 521

Dimensions of the packed product

(HxWxD) (mm)

130 x 580 x 600

Net weight (kg)

10.198

Gross weight (kg)

Residual heat indicator

Location of control panel

External control

Basic surface material Ceramic

Color of surface

Black Color of frame

Approval certificates

AENOR, CE

Length electrical supply cord (cm)

Connection rating (W)

Gas connection rating (W) Current (A)

Voltage (V) 220-240

Frequency (Hz)

60: 50

Consumption and connection features

2021-02-24

Page 1



Cl422101 Flex induction cooktop 400 series Frameless Width 38 cm

For combination within the set CVL 410

2021-02-24 Page 2





