

Color Variants

Fully integrated

With flexible hinge

Included accessories

Optional accessories

DA041160

DA042030

GH045010

427 mm

m long)

GZ010011

rails

1 x baking tray spray head.

Cutlery drawer with smooth running

Holder for long-stemmed glasses

Handle bar with 2 mounts, stainless

steel, Length 45 cm, drilling distance

Extension for water inlet and outlet (2

Installation Accessories

Silvercare cartridge for all dishwashers

DF261165F

DF261165F Dishwasher 200 series Fully integrated

With flexible hinge

Height 86.5 cm

Optional door opening at the end of the programme to support the hygienic drying process 6 programmes with aqua sensor and 3 options, such as Power and Intensive:

Clean and dry dishes in 59 minutes Intensive cleaning in the lower basket while protecting glassware in the upper basket

Flexible basket system with smooth running rails on all levels TFT display for intuitive handling of all functions

Bright interior lighting Very quiet: 42 dB Agua stop with guarantee

Handling

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water.

Touch key operation. Information key with use indications. Time delay up to 24 hours

Visual and acoustic end of programme indicator. Info-Light.

Technical Features

Bright interior lighting. Glass protection. Load sensor. Automatic detergent function.

Regeneration electronics. Heat exchanger.

Continuous flow heater. Triple filter system.

Soft lock.

Aqua stop with guarantee. Home network integration for digital services (Home Connect) wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

Programmes

6 programmes: Auto 35 °C - 45 °C. Auto 45 °C - 65 °C.

Auto 65 °C - 75 °C.

Eco 50 °C

Quick wash 45 °C (29 min.).

Pre-rinse.

3 options:

Intensive.

Power.

Holiday.

Features

Flexible basket system with smooth running rails on all levels.

Upper basket:

Over extension.

Rackmatic with 3 levels, adjustable in height up to 5 cm.

6 folding spines.

4 folding racks.

2 glass support bars.

Lower basket:

8 folding spines

2 folding racks.

Dividable glass support.

Cutlery basket.

Maximum dish sizes (upper/lower basket)

29/28, 26.5/30.5 or 24/34 cm respectively.

Characteristics

Energy efficiency class

Cleaning performance

Water consumption (I)

Total annual energy consumption (kWh) Total annual water consumption (I)

Estimated annual consumption (220 standard cycles) energy (kWh)

Total annual water consumption (I) 220 days

Built-in / Free-standing

Built-in Removable top

Door panel options

Height with worktop (mm)

Height of the product (mm)

Adjustable feet

Yes - front only

Maximum adjustability feet (mm)

Adjustable plinth

Net weight (kg) 45,688

Gross weight (kg)

48.0

Connection Rating (W) 2400

Current (A)

Voltage (V) 220-240

Frequency (Hz)

Length electrical supply cord (cm)

Plug type

Gardy plug w/ earthing

Length inlet hose (cm)

Length outlet hose (cm)

Hidden heating element

Water protection system description

Triple water protection 24h

No

Water softener

Yes

Top basket type

Adjustable upper basket

Rackmatic 3-stage

Upper rack cup shelf Bottom basket type

Lower rack cup shelf

3rd Rack

None

Silverware Basket

Standard

Optional accessories

DA041160, DA042030, DA043000

Included accessories 2

baking-sheet spray head grey, s/s decorative strips, vapor barrier plate

Number of place settings

Color / Material panel

Grey Color / Material body

Color / Material top

Dimensions of the packed product (HxWxD) (mm)

920 x 670 x 660

Consumption and connection features Brand

Gaggenau

Product name / Commercial code

Number of place settings

Energy efficiency class - NEW (2010/30/EC)

12 place setting capacity. Maximum glass loading capacity 23 wine glasses.

Consumption data

Energy efficiency class A++ at a range of energy efficiency classes from A++ + to D.

From 9.5 I water.

From 0.9 kWh.

Noise level 42 dB (re 1 pW).

Planning notes

Height-adjustable feet. Appliance plinth recess 100 mm (see drawing).

Rear feet adjustable at front. Door weight up to 10 kg. Door panel dimension dependent on plinth height of kitchen furniture. For installation into a tall unit.

ventilation openings are recommended


(min. 200 cm²). Connection

Total connected load 2.4 kW. Connecting cable pluggable. Water connection with 3/4" screw joint. Connection to hot or cold water possible.

Power consumption standby/network


Power consumption left-on-mode 0.5 W. Power consumption off-mode 0.5 W. Time auto-standby/network 2 min. Left-on-mode duration 0 min. Please check the user manual for how to switch off the WiFi module.

DF261165F
Dishwasher 200 series
Fully integrated
With flexible hinge
Height 86.5 cm
2019-10-24
Page 2



() Werte mit Verlängerungssatz

Connection dimensions for a 60 cm wide dishwasher



() values with extension kit

86.5 cm high dishwasher with flexible hinge

