

Color Variants DF480161F Fully integrated With flexible hinge

Included accessories

1 x baking tray spray head. 1 x GN container insert. 1 x glass holder rack.

Optional accessories DA041160 Cutlery drawer with smooth running rails DA042030 Silvercare cartridge for all dishwashers DA043000 Holder for long-stemmed glasses

Installation Accessories GZ010011 Extension for water inlet and outlet (2 m long)

DF480161F
Dishwasher 400 series
Fully integrated
With flexible hinge
Height 81.5 cm

Optimal protection for sensitive glassware by low temperature drving with zeolite and intelligent water softening 8 programmes with aqua sensor and 6 options, such as Power and Intensive: Clean and dry dishes in 57 minutes Intensive cleaning in the lower basket while protecting glassware in the upper basket Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket TFT display for intuitive handling of all functions Perfectly illuminated interior Push-to-open function for perfect integration into handleless furniture fronts Very quiet: 43 dB Energy efficiency class A+++ Aqua stop with guarantee

Handling

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water. Touch key operation. Information key with use indications. Time delay up to 24 hours. Visual and acoustic end of programme indicator. Info-Light.

Technical Features

Perfectly illuminated interior. Glass protection with zeolite. Aqua sensor. Load sensor. Detergent recognition. Regeneration electronics. Heat exchanger. Continuous flow heater. Triple filter system. Soft lock. Aqua stop with guarantee.

Programmes

8 programmes: Auto 35 °C - 45 °C. Auto 45 °C - 65 °C. Auto 65 °C - 75 °C. Intensive 70 °C. Eco 50 °C. Night programme. Quick wash 45 °C (29 min.). Pre-rinse. 6 options: Intensive. Power. Half Load Hygiene. Extra Dry. Energy Save.

Features

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket. Upper basket: Over extension. Rackmatic with 3 levels, adjustable in height up to 5 cm. 6 folding spines. 4 folding racks. 2 glass support bars. Lower basket: 8 folding spines. 2 folding racks. Dividable glass support. Cutlery basket. Holder for long-stemmed glasses.

Characteristics

Energy efficiency class Cleaning performance

Water consumption (I) 9.5 Total annual energy consumption (kWh) Total annual water consumption (I) Estimated annual consumption (220 standard cycles) energy (kWh) 176 Total annual water consumption (I) 220 days 2090 Built-in / Free-standing Built-in Removable top No Door panel options Not possible Height with worktop (mm) Height of the product (mm) Adjustable feet Yes - front only Maximum adjustability feet (mm) 60 Adjustable plinth Net weight (kg) 52.270 Gross weight (kg) 55.0 Connection Rating (W) 2400 Current (A) 10 Voltage (V) 220-240 Frequency (Hz) 50:60 Length electrical supply cord (cm) 175 Plug type Gardy plug w/ earthing Length inlet hose (cm) Length outlet hose (cm) 190 Hidden heating element Water protection system description Triple water protection 24h Water softener Top basket type Adjustable upper basket Rackmatic 3-stage Upper rack cup shelf Bottom basket type Lower rack cup shelf 3rd Rack None Silverware Basket Standard

Optional accessories DA041160, DA042030, DA043000 Included accessories 2 baking-sheet spray head grey. Glasstray, rack gastronorm insert, s/s decorative strips, vapor barrier plate Number of place settings Color / Material panel Grey Color / Material body Color / Material top

Dimensions of the packed product (HxWxD) (mm) 880 x 670 x 660

Consumption and connection features Brand Gaggenau Product name / Commercial code DF480161F Number of place settings Energy efficiency class - NEW (2010/30/EC)

Maximum dish sizes (upper/lower basket) 27/25, 24.5/27.5 or 22/31 cm respectively. 12 place setting capacity. Maximum glass loading capacity 23 wine glasses.

Consumption data


Energy efficiency class A+++ at a range of energy efficiency classes from A++ + to D. From 9.5 I water. From 0.8 kwh Noise level 43 dB (re 1 pW).


Planning notes

Height-adjustable feet. Appliance plinth recess 100 mm (see drawing). Rear feet adjustable at front. Door weight up to 8.5 kg. Door panel dimension dependent on plinth height of kitchen furniture. Installation and usage also with furniture handle possible. The push-toopen function remains active. For installation into a tall unit. ventilation openings are recommended (min. 200 cm²).

Connection


Total connected load 2.4 kW. Connecting cable pluggable. Water connection with 3/4" screw joint. Connection to hot or cold water possible.





() Werte mit Verlängerungssatz

Connection dimensions for a 60 cm wide dishwasher



81.5 cm high dishwasher with flexible hinge

