

Color Variants

DF480162F Fully integrated With flexible hinge

Included accessories

- 1 x baking tray spray head.
- 1 x GN container insert.
- 1 x glass holder rack.

Optional accessories

DA041160

Cutlery drawer with smooth running rails

DA042030

Silvercare cartridge for all dishwashers

DA043000

Holder for long-stemmed glasses

Installation Accessories

GZ010011

Extension for water inlet and outlet (2 m long)

DF480162F Dishwasher 400 series

Fully integrated

With flexible hinge

Height 81.5 cm

Optimal protection for sensitive glassware by low temperature drying with zeolite and intelligent water softening

8 programmes with aqua sensor and 5 options, such as Power and Intensive:

Clean and dry dishes in 57 minutes Intensive cleaning in the lower basket while protecting glassware in the upper basket

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket

TFT display for intuitive handling of all functions

Perfectly illuminated interior Push-to-open function for perfect integration into handleless furniture fronts

Very quiet: 43 dB Energy efficiency class A+++ Aqua stop with guarantee

Handling

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water.

Touch key operation. Information key with use indications. Time delay up to 24 hours.

Visual and acoustic end of programme indicator. Info-Light.

Technical Features

Perfectly illuminated interior. Glass protection with zeolite.

Agua sensor. Load sensor.

Automatic detergent function.

Regeneration electronics.

Heat exchanger. Continuous flow heater.

Triple filter system.

Soft lock.

Agua stop with guarantee. Home network integration for digital

services (Home Connect) wireless via

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

Programmes

8 programmes:

Auto 35 °C - 45 °C.

Auto 45 °C - 65 °C.

Auto 65 °C - 75 °C.

Intensive 70 °C.

Eco 50 °C.

Night programme.

Quick wash 45 °C (29 min.).

Pre-rinse.

5 options:

Intensive.

Power. Half Load.

Hygiene.

Extra Dry.

Features

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket.

Upper basket:

Over extension.

Rackmatic with 3 levels, adjustable in height up to 5 cm.

6 folding spines.

4 folding racks.

Characteristics

Energy efficiency class

Cleaning performance

Water consumption (I)

Total annual energy consumption (kWh) Estimated annual consumption (220 standard cycles) energy (kWh)

Total annual water consumption (I) 220 days

2090

Built-in / Free-standing Built-in

Removable top

Door panel options

Not possible Height with worktop (mm)

Height of the product (mm)

Adjustable feet

Maximum adjustability feet (mm)

Adjustable plinth

Net weight (kg) 52.770

Gross weight (kg)

Connection Rating (W)

55.0

Current (A)

Voltage (V)

220-240 Frequency (Hz)

50:60

Length electrical supply cord (cm)

Plug type Gardy plug w/ earthing

Length inlet hose (cm)

Length outlet hose (cm)

Hidden heating element

Water protection system description

Triple water protection 24h

Water softener

Yes

Top basket type Adjustable upper basket

Rackmatic 3-stage

Upper rack cup shelf

Bottom basket type Lower rack cup shelf

3rd Rack

None

Silverware Basket

Standard

Optional accessories

DA041160, DA042030, DA043000

Included accessories 2

baking-sheet spray head grey. Glasstray, rack gastronorm insert, s/s decorative strips, vapor barrier plate

Number of place settings

Color / Material panel Grev

Color / Material body

Color / Material top Dimensions of the packed product

(HxWxD) (mm) 880 x 670 x 660

Consumption and connection features

Gaggenau

Product name / Commercial code

DF480162F

Number of place settings

Energy efficiency class - NEW (2010/30/EC)

Energy consumption annual (kWh/

Lower basket:

8 folding spines.

2 folding racks.

Dividable glass support.

Cutlery basket.

Holder for long-stemmed glasses. Maximum dish sizes (upper/lower

27/25, 24.5/27.5 or 22/31 cm respectively.

12 place setting capacity. Maximum glass loading capacity 23 wine glasses.

Consumption data

Energy efficiency class A+++ at a range of energy efficiency classes from A++

From 9.5 I water.

From 0.8 kWh.

Noise level 43 dB (re 1 pW).

Planning notes

Height-adjustable feet. Appliance plinth recess 100 mm (see

drawing). Rear feet adjustable at front. Door weight up to 8.5 kg. Door panel dimension dependent on plinth height of kitchen furniture. Installation and usage also with furniture handle possible. The push-toopen function remains active. For installation into a tall unit, ventilation openings are recommended

Connection

(min. 200 cm²).


Total connected load 2.4 kW. Connecting cable pluggable. Water connection with 3/4" screw joint. Connection to hot or cold water

possible. Power consumption standby/network

Power consumption left-on-mode 0.5 W. Power consumption off-mode 0.5 W. Time auto-standby/network 2 min. Left-on-mode duration 0 min. Please check the user manual for how


to switch off the WiFi module.

DF480162F Dishwasher 400 series Fully integrated With flexible hinge Height 81.5 cm 2019-11-07 Page 2



() Werte mit Verlängerungssatz

Connection dimensions for a 60 cm wide dishwasher



() values with extension kit

81.5 cm high dishwasher with flexible hinge

