



Color Variants

EB333410
Stainless steel
Width 90 cm

Included accessories

1 x enamel baking tray.
suit. pyrolytic clean.
1 x rotary spit.
1 x grill shelf.
1 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA018105
Pull-out system
BA028115
Baking tray, enamelled
BA038105
Wire rack, chromium-plated
BA090100
Black rotary knobs for EB 333, set of 2

EB333410

Oven

Stainless steel

Width 90 cm

One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel
Cushioned door opening and closing system
Diagonally positioned light sources for optimal interior lighting
17 heating methods with core temperature probe, rotisserie spit and baking stone function
Hot air fan rotates in both directions for ideal heat distribution
TFT touch display
Panel-free appliance with control module behind glass
Electronic temperature control from 50 °C to 300 °C
83 litres net volume

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Option to save individual recipes (incl. core temperature probe).
Information key with use indicators.
Front-hinged door with 90° door opening angle.

Features

Core temperature probe with automatic shut-off.
Rotisserie spit.
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
2 x 10 W halogen light on the side.
Enamelled side shelf supports with 3 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

The door panel surface of the appliance extends 40 mm from the furniture cavity.
The outer edge of the door handle extends 90 mm from the furniture cavity.

Characteristics

Color / Material Front
Stainless steel

Built-in / Free-standing
Built-in

Integrated Cleaning system
No

Required niche size for installation (HxWxD)
475-475 x 860-860 x 560

Dimensions of the product (mm)
480 x 890 x 550

Dimensions of the packed product (HxWxD) (mm)
710 x 720 x 1000

Control Panel Material
Stainless steel

Door Material
Stainless steel behind glass

Net weight (kg)
82.397

Usable volume of cavity (l)
83

Cooking method
Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, Top heating, 1/3 bottom heat., warming

First cavity material
Enamelled

Number of interior lights
3

Approval certificates
CE, VDE

Length electrical supply cord (cm)
180

Interior Lights - cavity 1
3

Pull-out system
Accessory

Clock function
Alarm, Off, On, timer

Included accessories
1 x enamel baking tray,suit. pyrolytic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages cavity 1 (W)

Broil Element Wattages cavity 1 (W)
3900

Convection Element Wattages cavity 1 (W)
1900

Microwave wattage cavity 1 (W)

Drawer wattage (W)

Consumption and connection features

Energy efficiency class - NEW (2010/30/EC)
A

Energy consumption per cycle conventional - NEW (2010/30/EC)

Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)

Energy consumption per cycle forced air convection - NEW (2010/30/EC)

Energy consumption gas oven per cycle forced air convection - NEW (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection Rating (W)
5330

Current (A)
21

Voltage (V)
200

Frequency (Hz)
60; 50

Plug type
Japan/Taiwan plug

Connecting cable type

Universal Product Code

Color / Material Front
Stainless steel

Alternative colors available

Energy input
Electric

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

Connection

Energy efficiency class A.
Total connected load 5.3 kW.
Connection cable 1.8 m without plug.

