



RB282304ID

Optional accessories

RA260000:

Heavy duty hinge support (RB 2x)

RA430100:

Storage container with lid, anthracite

installation accessories

Fridge-freezer combination 200 series

177.2 x 55.8 cm, soft close flat hinge

RB282304ID

– Cushioned door closing system allowing a soft and controlled door closure

– 3 climate zones incl. 1 fresh cooling drawer with manually adjustable humidity

Height adjustable safety glass shelves

Door racks with aluminium profiles

Innovative defrost technology:

- Reduced energy consumption due to new evaporator design - Faster defrosting and easier cleaning due to less severe and more uniform ice build-up - Safety glass shelf between freezer drawers

Cushioned door closing system allowing a soft and controlled door closure

Net volume 271 litres

Handling

Electronic temperature control with digital display.

Touch keys.

Technical features

Automatic defrosting with defrost water evaporation.

Cushioned door closing system from 20° door opening angle, integrated in door hinge.

Open-door and malfunction alarm.

Cooling

Fast cooling.

Temperature adjustable from +2 °C to +8 °C.

5 safety glass shelves, of which 1 is fully extendable and 4 height adjustable.

Wine and champagne rack for 4 bottles, can be completely folded.

1 large door rack with aluminium profile for bottles with flexible bottle holder.

4 door racks with aluminium profile.

Bright interior lighting with integrated glare-free side light elements.

Net volume 209 litres.

Fresh cooling

1 full width fresh cooling drawer.

Humidity can be adjusted manually.

Ideal for fruit and vegetables.

Freezing

Fast freezing.

Temperature adjustable from -24 °C to -14 °C.

4-star freezer compartment.

Defrost assistance.

Freezing capacity 5 kg/24 h.

Storage time after a malfunction 26 h.

2 freezer drawers, 1 of which extra large.

1 safety glass shelf.

Net volume 61 litres.

Consumption data

Energy efficiency class A++.

Energy consumption 276 kWh/year.

Noise level 38 dB (re 1 pW).

Planning notes

Flat hinge.

Door hinge right, reversible.

Door opening angle of 115°, fixable at 90°.

Max. door panel weight:

Upper door 19 kg. Lower door 19 kg.

Connection

Total connected load: 0.090 KW.

Connecting cable 2.3 m with plug.

