



#### Color Variants

RB292311

With fresh cooling

Freestanding, stainless steel-backed full glass doors

#### Included accessories

- 2 x cold accumulator.
- 1 x berry tray.
- 2 x egg tray.
- 1 x wine and champagne rack.
- 1 x glass tray.
- 1 x ice cube tray.

#### Optional accessories

RA430100

Storage container with transparent lid, anthracite.

RB292311

Fridge-freezer combination 200 series

With fresh cooling

Freestanding, stainless steel-backed full glass doors

Width 70 cm, height 200 cm

4 climate zones incl. fresh cooling  
Height adjustable safety glass shelves  
Door racks with aluminium profiles  
Net volume 395 litres

#### Handling

Electronic temperature control with digital temperature display.  
Touch keys.

#### Technical Features

Dynamic cold air distribution.  
Automatic defrosting with defrost water evaporation.  
Open-door and malfunction alarm.  
Activated charcoal air filter.  
Stainless steel top and side panels.

#### Cooling

No-Frost technology with fast cooling.  
Temperature adjustable from +2 °C to +8 °C.  
4 safety glass shelves, 3 of which are height adjustable.  
Bright interior lighting with integrated glare-free side light elements.  
1 large door rack for bottles.  
5 door racks.  
Net volume 267 litres.

#### Fresh cooling

1 full width humidity drawer for vegetables, manually controllable.  
1 full width fresh cooling drawer.  
Net volume 36 litres.

#### Freezing

No-frost technology with fast freezing.  
Temperature adjustable from -16 °C to -24 °C.  
4-star freezer compartment.  
Automatic defrosting with defrost water evaporation.  
Freezing capacity 15 kg/24 h.  
Storage time after a malfunction 16 h.  
3 freezer drawers.  
Net volume 92 litres.

#### Consumption data

Energy efficiency class A++ at a range of energy efficiency classes from A++ to D.  
Energy consumption 284 kWh/year.  
Noise level 43 dB (re 1 pW).

#### Planning notes

Door hinge right, reversible.  
Wall recess of 20 mm necessary.  
Door opening angle of 125°, fixable at 90°.  
90 mm clearance hinge side for 90° door opening, 400 mm for 125° door opening and 65 mm handle side necessary.  
If integrated in a kitchenette the body of the appliance needs a front overlap of 15 mm. Alternatively an intermediate panel can be used on the hinge side with a recess of 15 mm and a width of min. 30 mm.  
Front feet are height-adjustable, casters at the back.

#### Connection

Total connected load 0.150 kW.  
Connecting cable 2.4 m with plug.

#### Characteristics

Built-in / Free-standing

Free-standing

Number of compressors

1

Number of independent cooling systems

2

Width of the product (mm)

700

Height (mm)

2000

Depth of the product

650

Net weight (kg)

105,661

Required niche size for installation (HxWxD)

Door panel options

Not possible

Door hinge

Right reversible

Number of Adjustable Shelves in fridge compartment

3

Shelves for Bottles

Yes

Frost free system

Full

Interior ventilator

No

Reversible Door Hinge

Yes

Length electrical supply cord (cm)

240

Noise level (dB)

43

Multi-Flow Air Tower

Yes

Fast cooling switch

Yes

Fast freezing switch

Yes

Temperature Controlled Drawer

Humidity Control Drawer

Number of Door Bins - Refrigerator

6

Door bin adjustability - Refrigerator

Tilt-out door bins in fridge

Gallon Storage

Yes

Number of Gallon storage

1

Motorized Shelf

No

Material of the shelves

Safety glass

Type of Light

Door opened indicator freezer

Yes

Drawers with telescopic rails

Automatic motor-driven ice-maker

No

Ice Storage Capacity (lbs)

Ice Cubes per Day (lbs)

#### Consumption and connection features

Connection Rating (W)

150

Current (A)

10

Voltage (V)

220-240

Frequency (Hz)

50

Energy consumption (kWh)

Freezing capacity (kg)

Storage Period in Event of Power Failure (h)

16

Approval certificates

CE, VDE

Universal Product Code

825225956846

Main colour of product

Stainless steel

Door panel options

Not possible

Noise level (dB)

43

Total annual energy consumption (kWh)

RB292311  
Fridge-freezer combination 200 series  
With fresh cooling  
Freestanding, stainless steel-backed  
full glass doors  
Width 70 cm, height 200 cm  
2019-08-29  
Page 2

