



Color Variants

RB472704

With fresh cooling close to 0 °C

Fully integrated

Included accessories

1 x egg box with lid.

1 x ice cube scoop.

Optional accessories

RA430100

Storage container with transparent lid, anthracite.

Installation Accessories

RA421715

Stainless steel door panels with handles

RA423340

Side trims, 2 pieces, for RY and RB.

RA425110

Handle bar, stainless steel, long

RA425710

Handle bar, stainless steel, short

RA428715

Stainless steel door panels, handleless

RA460000

RA460012

RA460030

Connecting element for vertically split fronts (for fridge-freezer combination).

RB472704

Vario fridge-freezer combination 400 series

With fresh cooling close to 0 °C

Fully integrated

Niche width 76.2 cm, Niche height 213.4 cm

Cooling section with one door and one fully extendable freezing drawer

Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front
 2. Pull-to-open function to facilitate opening the door using a handle
- Flat stainless steel inner door, full-length

Almost invisible rail system for shelves and door racks for flexible positioning
Solid anthracite aluminium door racks
1 fresh cooling drawer close to 0 °C with manually adjustable temperature and 1 fresh cooling drawer with manually adjustable humidity
Integrated ice maker with fixed inlet water connection
Fully extendable freezer drawer with practical divider in anthracite
TFT touch display
Net volume 452 litres
Energy Star qualified

Handling

TFT touch display operation.
Clear text display.

Technical Features

Dynamic cold air distribution.
Automatic defrosting with defrost water evaporation.
Cushioned door closing system.
Activated charcoal air filter.
Rest mode certified by Star-K.
When rest mode is active, the appliance can only be opened using a handle.
Open-door and malfunction alarm.
Home network integration for digital services (Home Connect) wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Cooling

No-Frost technology with fast cooling.
Temperature adjustable from +2 °C to +8 °C.
3 safety glass shelves, white glass, 2 of which are individually adjustable in height.
4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.
Flat door rail system with fully flexible positioning of door racks.
3 height adjustable door racks, 1 of which is extra deep.
Net volume 324 litres.

Fresh cooling close to 0 °C

1 fully extendable fresh cooling drawer close to 0 °C with transparent front, illuminated.
Cushioned closing system.
Temperature can be adjusted manually.
Ideal for meat, fish and poultry.
Net volume 0 litres.

Fresh cooling

1 fully extendable fresh cooling drawer with transparent front, illuminated.
Cushioned closing system.
Humidity can be adjusted manually.

Characteristics

Built-in / Free-standing

Built-in

Number of compressors

2

Number of independent cooling systems

2

Width of the product

756

Height

2125

Depth of the product

608

Net weight

193.630

Required niche size for installation (HxWxD)

2134.0 x 762.0 x 610

Door panel options

Not possible

Door hinge

Right reversible

Number of Adjustable Shelves in fridge compartment

2

Shelves for Bottles

No

Frost free system

Interior ventilator

Yes

Reversible Door Hinge

Yes

Length electrical supply cord

300

Noise level

42

Multi-Flow Air Tower

Yes

Fast cooling switch

Yes

Fast freezing switch

No

Carbon Air Filter

No

Temperature Controlled Drawer

No

Humidity Control Drawer

Yes

Number of Door Bins - Refrigerator

3

Door bin adjustability - Refrigerator

No

Tilt-out door bins in fridge

No

Number of Gallon storage

1

No. of shelves in fridge

3

Number of shelves - Freezer

Shelf Adjustability - Freezer

No

Capacity of Water Tank

Connection rating

350

Fuse protection

10

Voltage

110-120

Frequency

60

Energy consumption

Freezing capacity

Energy efficiency rating

Energy consumption annual - NEW (2010/30/EC)

Refrigerator Net capacity - NEW (2010/30/EC)

Freezer Net capacity - NEW (2010/30/EC)

0

Frost free system

Freezing capacity) - NEW (2010/30/EC)

0

Storage Period in Event of Power Failure (h)

Approval certificates

CSA

Universal Product Code

825225922490

Color / Material body

Door panel options

Ideal for fruit and vegetables.

Freezing

No-frost technology with fast freezing at -30 °C.
Temperature adjustable from -14 °C to -24 °C.
4-star freezer compartment.
Freezing capacity 5.8 kg/24 h.
2 fully extendable drawers, one of them inside. Outer drawer with synchronously running pull-out rails.
Interior lighting with 2 LED light spots, warm white light.
Net volume 128 litres.

Ice maker

Integrated in the freezer compartment, with fixed inlet water connection.
Particle filter for water inlet, integrated in ventilation grille area.
Can be switched off.
Ice cube production approx. 1.3 kg/24 h.
Removable ice storage container with approx. 3 kg capacity.

Consumption data

Energy consumption 511 kWh /year.
Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, fixable at 90°.
Max. door panel weight:
Door 41 kg.
Drawer 10 kg.
Shut-off valve for water connection must be planned next to the appliance and always be accessible.
If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

Connection

Total connected load 0.350 KW.
Total Amps: 10 A.
Connecting cable 3.0 m, pluggable.
Water inlet.
Supply hose 1.3 m with 3/4" connection.
Water pressure 2 to 8 bar.

GAGGENAU

RB472704

Vario fridge-freezer combination 400 series

With fresh cooling close to 0 °C



Fully integrated

Niche width 76.2 cm, Niche height 213.4 cm

Cooling section with one door and one fully extendable freezing drawer

2021-10-15

Page 2



The maximum door front dimensions are based on a clearance of 3/8th in.