

Color Variants RC242203 With fresh cooling close to 0 °C Fully integrated

Included accessories

2 x egg tray. 1 x wine and champagne rack.

Optional accessories

RA430100 Storage container with transparent lid, anthracite.

RC242203

Refrigerator 200 series With fresh cooling close to 0 °C Fully integrated Niche width 56 cm, Niche height 140 cm

2 climate zones incl. fresh cooling close to 0 °C Height adjustable safety glass shelves Door racks with aluminium profiles Cushioned door closing system allowing a soft and controlled door closure Net volume 222 litres

Handling

Electronic temperature control with digital display. Touch keys.

Technical Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation. Cushioned door closing system from 20° door opening angle, integrated in door hinge. Open-door and malfunction alarm.

Cooling

Temperature adjustable from +3 °C to +8 °C. 4 safety glass shelves, of which 1 is fully extendable and 4 height adjustable. 1 integrated shelf. Wine and champagne rack for 4 bottles, can be completely folded away. 1 large door rack with aluminium profile for bottles with flexible bottle holder. 3 door racks with aluminium profile. Bright interior lighting with integrated glare-free side light elements. Net volume 163 litres.

Fresh cooling close to 0 °C

1 full width fresh cooling drawer close to 0 °C. Humidity can be adjusted manually. Ideal for fruit and vegetables. Ideal for meat, fish and poultry. Net volume 59 litres.

Consumption data

Energy efficiency class A++ at a range of energy efficiency classes from A++ + to D. Energy consumption 124 kWh/year. Noise level 37 dB (re 1 pW).

Planning notes

Flat hinge. Door hinge right, reversible. Door opening angle of 115°, fixable at 90°. Max. door panel weight 14 kg.

Connection

Total connected load 0.090 KW. Connecting cable 2.3 m with plug. Characteristics Built-in / Free-standing Built-in

Number of compressors 1

Number of independent cooling systems

Width of the appliance 558 Height (mm) 1397

Depth of the product 545

Net weight (kg) 52.182

Required niche size for installation (HxWxD)

1400 x 560 x 550 Door panel options

Not possible Door hinge

Right reversible Number of Adjustable Shelves in fridge compartment

Shelves for Bottles

Yes Frost free system

No Interior ventilator

No

Reversible Door Hinge Yes

Length electrical supply cord (cm) 230

Noise level (dB) 37

Multi-Flow Air Tower

Economy setting No

Cold technology 1 compressor/2 cold circuits

Fast cooling switch Yes

Temperature Controlled Drawer

Humidity Control Drawer Yes

Number of Door Bins - Refrigerator

Door bin adjustability - Refrigerator No

Tilt-out door bins in fridge

Gallon Storage Yes

Number of Gallon storage

No. of shelves in fridge

Motorized Shelf

No Material ofthe shelves Glas, plastic Type of Light

Door opened indicator freezer Yes

Connection rating (W) 90

Current (A)

Voltage (V) 220-240

50

Frequency (Hz)

Energy consumption (kWh) Freezing capacity (kg)

Storage Period in Event of Power Failure (h)

Approval certificates

CE, VDE Universal Product Code Main colour of product

N/A Door panel options Not possible Installation typology

Full-integrated Noise level (dB) 37









