



**RF463702**  
**Vario freezer 400 series**  
**fully integrated**  
**Niche width 61 cm, Niche height 213.4 cm**  
**Right-hinged**

**Stainless steel interior**  
**Generous lighting concept**  
**Integrated ice maker with fixed inlet water connection**  
**Illuminated dispenser for ice cubes, crushed ice and chilled water**  
**Solid aluminium door racks**  
**Net volume 320 litres**

**Handling**  
 Electronic temperature control with digital display.

**Technical Features**  
 Dynamic cold air distribution.  
 Automatic defrosting with defrost water evaporation.  
 Rest mode certified by Star-K.  
 Open-door and malfunction alarm.

**Freezing**  
 No-frost technology with fast freezing. Temperature adjustable from +7 °F to -9 °F (-14 °C to -23 °C).  
 4-star freezer compartment.  
 4 solid metal shelves, 2 of which are manually adjustable.  
 2 fully extendable drawers with transparent front, 1 of which large, 1 regular.  
 Bright interior lighting with light pillars.  
 1 extra deep door rack.  
 1 door rack with transparent front flap.

**Ice and water dispenser**  
 Illuminated.  
 Integrated, with fixed inlet water connection.  
 Can be switched off.  
 Ice cube production approx. 1.9 kg/24 h.  
 Ice cubes and crushed ice.  
 Removable ice storage container with approx. 3 kg capacity.  
 Ice water supply approx. 1.5 litres.

**Consumption data**  
 Energy consumption 493.85 kwh/year.  
 Energy consumption 1.353 kwh/24 h.  
 Noise level 39 dB (re 1 pW).

**Planning notes**  
 Flat hinge.  
 Door opening angle of 115°, fixable at 90°.  
 Max. door panel weight 57 kg.  
 Shut-off valve for water connection must be planned next to the appliance and always be accessible.  
 If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

**Connection**  
 Total connected load 0.565 kW.  
 Connecting cable 118,1" (3.0 m) with plug.  
 Water inlet.  
 Water pressure 2 to 8 bar.

**Characteristics**  
**Product category**  
 Upright freezer  
**Built-in / Free-standing**  
 Built-in  
**Color / Material body**  
**Frost free system**  
 Full  
**Climate class**  
 T  
**Door panel options**  
**Width of the product (mm)**  
 603  
**Depth of the product**  
 608  
**Dimensions of the packed product (HxWxD) (mm)**  
 2260 x 750 x 700  
**Required niche size for installation (HxWxD)**  
 2134.0 x 610 x 610  
**Warning signal / malfunction**  
 No signal  
**Defrost process**  
**Cover door installation system**  
 Fixed-mounted  
**Number of drawers/baskets (Stck)**  
 2  
**Number of freezing flaps (Stck)**  
 0  
**Lockable door**  
 No  
**Thermometer freeze section**  
 Digital  
**Light**  
 Yes  
**Length electrical supply cord (cm)**  
 300  
**Door hinge**  
 Right  
**Net weight (kg)**  
 157.902  
**Gross weight (kg)**  
 173.0  
**Multi-Flow Air Tower**  
 Yes  
**Number of compressors**  
 1  
**Number of independent cooling systems**  
 1  
**Economy setting**  
 Yes  
**Fast freezing switch**  
 Yes  
**Number of Door Bins - Freezer**  
 2  
**Door bin adjustability - Freezer**  
 No  
**Tilt-out door bins in freezer**  
 Yes  
**Number of shelves - Freezer**  
 2  
**Door bin adjustability - Freezer**  
 No  
**Shelf Material - Freezer**  
 Metal  
**Reversible Door Hinge**  
 No  
**Consumption and connection features**  
**Connection Rating (W)**  
 565  
**Current (A)**  
 10  
**Frequency (Hz)**  
 60  
**Approval certificates**  
 CE, ETL, ETL, VDE  
**Energy consumption (kWh)**  
 1.35  
**Total annual energy consumption (kWh)**  
 493.8  
**Universal Product Code**  
 825225803126  
**Main colour of product**  
 N/A  
**Door panel options**  
**Installation typology**  
 N/A  
**Noise level (dB)**  
 -

**Color Variants**  
**RF463702**  
**fully integrated**  
**Niche width 61 cm, Niche height 213.4 cm**

**Optional accessories**  
**RA450000**  
**Mechanical particle filter.**  
**RA450010**  
**Activated charcoal filter for water filter system including saturation indicator.**

**Required installation accessories**  
**RA460010**  
**Additional side heating element.**  
**Required if appliances are installed handle to hinge or hinge to hinge. Not required if appliances are installed more than 160 mm apart from each other.**

**Installation Accessories**  
**RA422610**  
**Stainless steel door panel with handle**  
**RA425110**  
**Handle bar, stainless steel, long**  
**RA460020**  
**Connecting element for vertically split appliance fronts (for a flush front).**