



RF463703TW
Vario freezer 400 series
fully integrated
Niche width 61 cm, Niche height 213.4 cm
Left-hinged

Stainless steel interior
Generous lighting concept
Integrated ice maker with fixed inlet water connection
Illuminated dispenser for ice cubes, crushed ice and chilled water
Solid aluminium door racks
Net volume 320 litres

Handling
 Electronic temperature control with digital display.

Technical Features
 Dynamic cold air distribution.
 Automatic defrosting with defrost water evaporation.
 Rest mode certified by Star-K.
 Open-door and malfunction alarm.

Freezing
 No-frost technology with fast freezing. Temperature adjustable from -14 °C to -25 °C.
 4-star freezer compartment.
 4 solid metal shelves, 2 of which are manually adjustable.
 2 fully extendable drawers with transparent front, 1 of which large, 1 regular.
 Bright interior lighting with light pillars.
 1 extra deep door rack.
 1 door rack with transparent front flap.

Ice and water dispenser
 Illuminated.
 Integrated, with fixed inlet water connection.
 Can be switched off.
 Ice cube production approx. 1.9 kg/24 h.
 Ice cubes and crushed ice.
 Removable ice storage container with approx. 3 kg capacity.
 Ice water supply approx. 1.5 litres.

Consumption data
 Energy consumption 493.85 kwh/year.
 Energy consumption 1.353 kwh/24 h.
 Noise level 39 dB (re 1 pW).

Planning notes
 Flat hinge.
 Door opening angle of 115°, fixable at 90°.
 Max. door panel weight 57 kg.
 Shut-off valve for water connection must be planned next to the appliance and always be accessible.
 If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

Connection
 Total connected load 0.565 kW.
 Connecting cable 139 1/3" (3.4 m) with plug.
 Water inlet.
 Water pressure 2 to 8 bar.

Characteristics
Product category
 Upright freezer
Built-in / Free-standing
 Built-in
Color / Material body
 Frost free system
 Full
Climate class
 T
Door panel options
Width of the product (mm)
 603
Depth of the product
 608
Dimensions of the packed product (HxWxD) (mm)
 2260 x 740 x 700
Required niche size for installation (HxWxD)
 2134.0 x 610 x 610
Warning signal / malfunction
 No signal
Defrost process
Cover door installation system
 Fixed-mounted
Number of drawers/baskets (Stck)
 2
Number of freezing flaps (Stck)
 0
Lockable door
 No
Thermometer freeze section
 Digital
Light
 Yes
Length electrical supply cord (cm)
 345
Door hinge
 Left
Net weight (kg)
 157.594
Gross weight (kg)
 173.0
Multi-Flow Air Tower
 Yes
Number of compressors
 1
Number of independent cooling systems
 1
Economy setting
 Yes
Fast freezing switch
 Yes
Number of Door Bins - Freezer
 2
Door bin adjustability - Freezer
 No
Tilt-out door bins in freezer
 Yes
Number of shelves - Freezer
 2
Door bin adjustability - Freezer
 No
Shelf Material - Freezer
 Metal
Reversible Door Hinge
 No
Consumption and connection features
Connection Rating (W)
 565
Current (A)
 10
Frequency (Hz)
 60
Approval certificates
 ETL, ETL
Energy consumption (kWh)
 1.35
Total annual energy consumption (kWh)
 493.8
Universal Product Code
Main colour of product
 N/A
Door panel options
Installation typology
 N/A
Noise level (dB)
 39

Color Variants
RF463703TW
fully integrated
Niche width 61 cm, Niche height 213.4 cm

Optional accessories
RA450000
Mechanical particle filter.
RA450010
Activated charcoal filter for water filter system including saturation indicator.

Required installation accessories
RA460010
Additional side heating element.
Required if appliances are installed handle to hinge or hinge to hinge. Not required if appliances are installed more than 160 mm apart from each other.

Installation Accessories
RA422610
Stainless steel door panel with handle
RA425110
Handle bar, stainless steel, long
RA460020
Connecting element for vertically split appliance fronts (for a flush front).

