



RF491704
Vario freezer 400 series
Fully integrated, with ice maker
Niche width 91.4 cm, Niche height 213.4 cm

Stainless steel interior with solid anthracite aluminium elements
 Warm white and glare-free LED light spots

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front

2. Pull-to-open function to facilitate opening the door using a handle

The drawers in the RC and RF models are positioned at the same height.

With side-by-side installation, the glass shelves and door racks can be aligned on the same level

Material and aesthetics of interior as for RC model

- Glass shelves

- Solid anthracite aluminium door racks

Flat stainless steel inner door, full-length

Almost invisible rail system for shelves and door racks for flexible positioning

Integrated ice maker with fixed inlet water connection

TFT touch display

Net volume 550 litres

Energy Star qualified

Handling

TFT touch display operation.

Clear text display.

Technical Features

Dynamic cold air distribution.

Automatic defrosting with defrost water evaporation.

Cushioned door closing system.

Rest mode certified by Star-K.

When rest mode is active, the appliance can only be opened using a handle.

Open-door and malfunction alarm.

Home network integration for digital services (Home Connect) wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Freezing

No-frost technology with fast freezing at -30 °C.

Temperature adjustable from -14 °C to -24 °C.

4-star freezer compartment.

Freezing capacity 10.7 kg/24 h.

4 safety glass shelves, white glass, 3 of which are individually height adjustable. 2 fully extendable drawers with transparent front.

Brilliant LED light spots with warm white, glare-free light.

Flat door rail system with fully flexible positioning of door racks.

4 height-adjustable door racks.

Ice maker

Integrated in the freezer compartment, with fixed inlet water connection.

Particle filter for water inlet, integrated in ventilation grille area.

Can be switched off.

Ice cube production approx. 1.4 kg/24 h.

Removable ice storage container with approx. 2.5 kg capacity.

Characteristics

Product category

Upright freezer

Built-in / Free-standing

Built-in

Color / Material body

Frost free system

Full

Climate class

SN-T

Door panel options

Width of the appliance

908

Depth of the product

608

Dimensions of the packed product

(HxWxD)

2270 x 740 x 1000

Required niche size for installation

(HxWxD)

2134.0 x 914.0 x 610

Warning signal / malfunction

Defrost process

Cover door installation system

Fixed-mounted

Number of drawers/baskets (Stck)

2

Number of freezing flaps (Stck)

0

Lockable door

No

Thermometer freeze section

Light

Yes

Length electrical supply cord

300

Door hinge

Left reversible

Net weight

191.365

Gross weight

210.7

Multi-Flow Air Tower

Yes

Number of compressors

1

Number of independent cooling systems

1

Economy setting

Yes

Fast freezing switch

No

Number of Door Bins - Freezer

3

Door bin adjustability - Freezer

Yes

Tilt-out door bins in freezer

No

Number of shelves - Freezer

3

Door bin adjustability - Freezer

Yes

Shelf Material - Freezer

Safety glass

Reversible Door Hinge

Yes

Connection rating

350

Fuse protection

10

Frequency

60

Approval certificates

CSA

Energy consumption

Total annual energy consumption

Energy efficiency rating

Energy consumption annual - NEW

(2010/30/EC)

Refrigerator Net capacity - NEW

(2010/30/EC)

Freezer Net capacity - NEW (2010/30/

EC)

0

Frost free system

Full

Freezing capacity) - NEW (2010/30/EC)

0

Universal Product Code

825225922698

Main colour of product

Consumption data

Energy consumption 543 kWh /year.

Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.

Door hinge left, reversible.

Door opening angle of 115°, fixable at 90°.

In case of door opening angle of 90° the standard ice storage container cannot be taken out. To make it possible it has to be exchanged for the small ice storage container (RA44822).

This change must be done prior to fixing the door.

Max. door panel weight 43 kg.

Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

Water inlet.

Supply hose 1.2 m with 3/4" connection.

Water pressure 2 to 8 bar.

Connection

Total connected load 0.350 KW.

Total Amps: 10 A.

Connecting cable 3.0 m, pluggable.

Water inlet.

Supply hose 1.2 m with 3/4" connection.

Water pressure 2 to 8 bar.

Color Variants

RF491704

Fully integrated, with ice maker

Niche width 91.4 cm, Niche height 213.4 cm

cm

Included accessories

1 x ice cube scoop.

1 x connection set.

1 x Ice storage container.

large.

Optional accessories

RA448220

Ice storage container, small.

Installation Accessories

RA421914

Stainless steel door panel with handle

RA423140

Side trims, long.

RA425110

Handle bar, stainless steel, long

RA428914

Stainless steel door panel, handleless

RA460012

RA460020

Connecting element for vertically split appliance fronts (for a flush front).

GAGGENAU

