

Color Variants

RT242203

With fresh cooling close to 0 °C Fully integrated

Included accessories

2 x egg trav.

1 x wine and champagne rack.

1 x ice cube tray.

Optional accessories

RA430100

Storage container with transparent lid, anthracite.

RT242203

Fridge-freezer combination 200 series

With fresh cooling close to 0 °C

Fully integrated

Niche width 56 cm, Niche height 140

3 climate zones incl. fresh cooling close to 0 °C

Height adjustable safety glass shelves Door racks with aluminium profiles Cushioned door closing system allowing a soft and controlled door closure

Net volume 204 litres

Handling

Electronic temperature control with digital display. Touch keys.

Technical Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation.

Cushioned door closing system from 20° door opening angle, integrated in door hinge.

Open-door and malfunction alarm.

Cooling

Temperature adjustable from +3 °C to +8 °C.

3 safety glass shelves, of which 1 is fully extendable and 3 height adjustable.

1 integrated shelf.

Wine and champagne rack for 4 bottles, can be completely folded away. 1 large door rack with aluminium profile for bottles with flexible bottle holder. 3 door racks with aluminium profile. Bright interior lighting with integrated glare-free side light elements. Net volume 130 litres.

Fresh cooling close to 0 $^{\circ}\text{C}$

1 full width fresh cooling drawer close to 0 °C.

Humidity can be adjusted manually. Ideal for fruit and vegetables. Ideal for meat, fish and poultry. Net volume 59 litres.

Freezing

Fast freezing.

Storage temperature -18 °C and lower. 4-star freezer compartment. Freezing capacity 2.5 kg/24 h Storage time after a malfunction 13 h. Net volume 15 litres.

Consumption data

Energy efficiency class A++ at a range of energy efficiency classes from A+ + to D.

Energy consumption 196 kWh/year. Noise level 38 dB (re 1 pW).

Planning notes

Flat hinge

Door hinge right, reversible. Door opening angle of 115°, fixable at 90°

Max. door panel weight 14 kg.

Connection

Total connected load 0.090 KW. Connecting cable 2.3 m with plug.

Characteristics

Built-in / Free-standing

Built-in

Number of compressors

Number of independent cooling systems

Width of the appliance

Height (mm) 1397

Depth of the product

545

Net weight (kg)

54.733

Required niche size for installation (HxWxD)

1400 x 560 x 550

Door panel options

Not possible

Door hinge

Right reversible

Number of Adjustable Shelves in fridge

compartment

Shelves for Bottles

Frost free system

No

Interior ventilator

No

Reversible Door Hinge

Length electrical supply cord (cm)

Noise level (dB)

38

Multi-Flow Air Tower No

Economy setting

No

Cold technology

1 compressor/2 cold circuits

Fast cooling switch

Temperature Controlled Drawer

Humidity Control Drawer

Number of Door Bins - Refrigerator

Door bin adjustability - Refrigerator

Tilt-out door bins in fridge

Gallon Storage

Number of Gallon storage

No. of shelves in fridge

Motorized Shelf

Material of the shelves

Glas, plastic

Type of Light

Door opened indicator freezer

Connection rating (W)

Current (A)

Voltage (V)

220-240 Frequency (Hz)

Energy consumption (kWh)

Freezing capacity (kg)

Storage Period in Event of Power Failure (h)

13

Approval certificates

CE, VDE

Universal Product Code

Main colour of product

Door panel options

Not possible

Installation typology Full-integrated

Noise level (dB)



RT242203 Fridge-freezer combination 200 series With fresh cooling close to 0 °C Fully integrated Niche width 56 cm, Niche height 140

2021-07-09 Page 2





