

## RW404761



## RA050200:

carbon air filter for RW 404/424

## RA491630:

Extendable bottle tray for RW 414

## Built-in wine cooler 200 series 23.5"

## RW404761

# Humidity level can be increased to avoid drying out of cork

 2 independently controllable climate zones
Consistent temperatures with exact control from +41 °F to +68 °F (+5 °C to + 20 °C)

Humidity control

Extendable bottle trays in beech and aluminium LED lighting

Cushioned door closing system allowing a soft and controlled door closure

Lockable door

Number of standard wine bottles: 34

#### Handling

Electronic temperature control with digital display.

Touch keys.

Presentation light option in each climate zone, dimmable.

Interior lighting with automatic dimming with opening and closing of door.

## Technical features

Dynamic cold air distribution.

Automatic defrosting with defrost water evaporation.

Cushioned door closing system integrated in door hinge.

1 activated charcoal air filter for both climate zones.

UV-protection.

Open-door and malfunction alarm.

Dust filter, dishwasher-safe.

## Features

Capacity 34 bottles (based on 0.75 I standard bottles).

5 bottle trays, 3 of which are extendable.

Storage of magnum bottles possible.

Net volume 4.3 cu. ft. (94 liters)

## Consumption data

Noise level 38 dB (re 1 pW).

## Planning notes

Flat hinge.

Door hinge right, reversible.

Height-adjustable feet.

Door opening angle 115°, fixable at 95°.

For integration next to a side wall a clearance of 150 mm hinge side is necessary.

The mains socket needs to be planned outside the built-in niche.

No transport/operation above 1500 m sea level.

## Connection

Total connected load 0.200 KW.

115 V / 60 Hz.

Total Amps: 10 A.

Connecting cable 70 7/8" (1.8 m) with plug.



