



Color Variants

RW464761
Fully integrated, with glass door
Niche width 24" (61 cm), Niche height 84" (213.4 cm)

Required installation accessories

RA460010
Additional side heating element.
Required if appliances are installed handle to hinge or hinge to hinge. Not required if appliances are installed more than 160 mm apart from each other.

Installation Accessories

RA420010
Door lock for RW 414, RW 464 and RW 466.
RA421611
Stainless steel door panel frame with handle
RA421612
Stainless steel door panel frame with handle
RA425110
Handle bar, stainless steel, long

RW464761
Vario wine climate cabinet 400 series
Fully integrated, with glass door
Niche width 24" (61 cm), Niche height 84" (213.4 cm)

2 independently controllable climate zones
Consistent temperatures with exact control from +41 °F to +68 °F (+5 °C to + 20 °C)
Humidity control
Stainless steel interior
Fully extendable bottle trays in beech and aluminium
Presentation light option
Low-vibration operation
Capacity 99 bottles

Handling

Electronic temperature control with digital display.

Technical Features

Dynamic cold air distribution.
Automatic defrosting with defrost water evaporation.
Activated charcoal air filter.
UV-protection.
Rest mode certified by Star-K.
Open-door and malfunction alarm.

Features

Net volume 13.7 cu. ft. (389 liters)
Capacity 99 bottles (based on 0.75/l standard bottles).
10 fully extendable bottle trays, up to 4 of which for storage of magnum bottles.
Space for max. 13 bottle trays or shelves in aluminium.
Interior lighting with 2 ceiling spots in each climate zone, can be used as presentation light.

Consumption data

Energy consumption 421 kwh/year.
Energy consumption 1.153 kwh/24 h.
Noise level 43 dB (re 1 pW).

Planning notes

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, fixable at 90°.
Max. door panel weight 72 kg.
No transport/operation above 1.500 m sea level.

Connection

Total connected load 0.102 kW.
120 V / 60 Hz.
Total Amps: 10 A.
Connecting cable 118,1" (3.0 m) with plug.

Characteristics
Built-in / Free-standing
Built-in
Door panel options
Not possible
Height (mm)
2125
Width of the product (mm)
603
Depth of the product
608
Required niche size for installation (HxWxD)
2134.0 x 610 x 610
Net weight (kg)
147.000
Connection Rating (W)
102
Current (A)
10
Voltage (V)
120
Frequency (Hz)
60
Approval certificates
CE, ETL, ETL, VDE
Length electrical supply cord (cm)
300
Plug type
120V-3 prong
Energy consumption (kWh/d) winecooler
1.15
Energy consumption per Year (kWh/a) winecooler
420.8
Total unit gross capacity (l)
389
Number of compressors
1
Number of independent cooling systems
1
Interior ventilator
Yes
Reversible Door Hinge
Yes
Interior light switch
No
Number of temperature zones
Range of temperature (°C)
5-20
Economy setting
Yes
Carbon Air Filter
No
Presenter Lighting
Yes
Presenter Shelf
Yes
Type of Glass Door
2 glass panels
Number of adjustable shelves
0
Number of shelves
10
Bottles per Shelf
7
Material ofthe shelves
Type of Light
Interior ventilator
Yes

Consumption and connection features
Brand
Gaggenau
Product name / Commercial code
RW464761
Product category
Winestorage
Energy efficiency class - NEW (2010/30/EC)
Energy consumption annual (kWh/ annum) - NEW (2010/30/EC)
Capacity in 0.75l (bordeaux bottles)
99
Climate class
T
Noise level (dB)
43
Universal Product Code
606650000000

