



#### Color Variants

VE230114

Stainless steel control panel

Width 28 cm

#### Included accessories

1 x glass scraper.

#### Optional accessories

VD201014

Brushed stainless steel appliance cover

#### Installation Accessories

SH230001

Hinge holder for fitting the appliance cover

VV200014

Stainless steel connection strip for combination with other Vario appliances of the 200 series

#### VE230114

Vario glass ceramic cooktop 200 series

Stainless steel control panel

Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity  
Generous control panel for comfortable and secure operation

#### Cooking zones

1 Super-Quick cooking zone  $\varnothing$  14.5 cm (1200 W).

1 Super-Quick cooking zone  $\varnothing$  12 cm (700 W), converts to  $\varnothing$  18 cm (1800 W) cooking zone.

#### Handling

Continuously variable energy controls.

#### Features

Cooking zone marking.

#### Safety

Individual residual heat indicators.  
Operation indicator.

#### Planning notes

Immersion depth 44 mm, depth at plug socket 65 mm.

Appliance can be snapped into the worktop from above.  
Appliance weight: approx. 6 kg.

#### Connection

Total connected load 3.0 kW.  
Connecting cable 1.7 m without plug.

#### Characteristics

Product name/family

Vario/Domino cooking zone cera

Built-in / Free-standing

CONSTR\_TYPE.Built-in

Energy input

Electric

Total number of positions that can be used at the same time

2

Required niche size for installation

(HxWxD)

65 x 268 x 490

Width of the product (mm)

288

Dimensions of the product (mm)

65 x 288 x 523

Dimensions of the packed product

(HxWxD) (mm)

177 x 405 x 604

Net weight (kg)

5.776

Gross weight (kg)

6.9

Residual heat indicator

Separate

Location of control panel

Hob front

Basic surface material

Ceramic

Color of surface

Black

Color of frame

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

170

#### Consumption and connection features

Electrical connection rating (W)

3000

Gas connection rating (W)

Current (A)

16

Voltage (V)


220-240

Frequency (Hz)

50; 60

2019-10-29

Page 1



Mounting rail  
(rear and front)

