



VE260114
Vario glass ceramic cooktop 200 series
Stainless steel control panel
Width 60 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
 Generous control panel for comfortable and secure operation

Cooking zones

2 Super-Quick cooking zones ø 18 cm (1800 W).
 2 Super-Quick cooking zones ø 14.5 cm (1200 W).

Handling

Continuously variable energy controls.

Features

Cooking zone marking.

Safety

Individual residual heat indicators.
 Operation indicator.

Planning notes

Immersion depth 58 mm.
 Under the appliance, a 60 mm clearance must be observed from side panels or intermediate shelf must be planned.
 Installation in a 60 cm wide bottom cabinet is possible.
 Appliance can be snapped into the worktop from above.
 Securing rail on the rear and the front.
 Appliance weight: approx. 10 kg.

Connection

Total connected load 6.0 kW.
 Plan a connection cable.

Characteristics

Product name/family
 Cooking zone ceramic

Construction type
 Built-in

Energy input
 Electric

Total number of positions that can be used at the same time
 4

Type of control setting devices
 Required niche size for installation (HxWxD)
 58 x 560-560 x 490-490

Width of the product (mm)
 580

Dimensions of the product (mm)
 58 x 580 x 523

Dimensions of the packed product (HxWxD) (mm)
 200 x 700 x 615

Net weight (kg)
 9.865

Gross weight (kg)
 12.5

Residual heat indicator
 Separate

Location of control panel
 Hob front

Type of external control possibility
 Basic surface material
 Ceramic

Color of surface
 Black, Black

Color of frame
 Black

Approval certificates
 CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)
 Knob Material
 Full metal

Sealed Burners
 No

heating with booster
 Type of pan support

Natural Gas Connection Rating (BTU)
LP Gas Connection Rating (BTU)
Dimension of 1st heating element (in)
Power of heating element (kW)
 1.8

Power of 1st burner (BTU)
Dimension of 2nd heating element (in)
Power of 2nd heating element (kW)
Power of 2nd burner (BTU)
Dimension of 3rd heating element (in)
Power of 3rd heating element (kW)
 1.2

Power of 3rd burner (BTU)
Dimension of 4th heating element (in)
Power of 4th heating element (kW)
Power of 4th burner (BTU)
Dimension of 5th heating element (in)
Power of 5th heating element (kW)
 1.8

Power of 5th burner (BTU)
Dimension of 6th heating element (in)
Power of heating element (kW in boost)
Power of 2nd heating element (kW in boost)
Power of 3rd heating element (kW in boost)
Power of 4th heating element (kW in boost)
Power of 5th heating element (kW in boost)
Power of 6th heating element (kW in boost)

Consumption and connection features
Electrical connection rating (W)
 6000

Gas connection rating (W)
Current (A)
 3*16

Voltage (V)
 230

Frequency (Hz)
 60; 50

Universal Product Code
 825225915867

Color Variants


VE260114
Stainless steel control panel
Width 60 cm

Included accessories

1 x glass scraper.

Installation Accessories

VV200014
Stainless steel connection strip for combination with other Vario appliances of the 200 series



Mounting rail
(rear and front)

