

**VE270114**  
**Vario glass ceramic cooktop 200 series**  
**Stainless steel control panel**  
**Width 70 cm**

Can be combined with the cooktops of the Vario 200 series to a harmonic unity  
Generous control panel for comfortable and secure operation

#### Cooking zones

1 Super-Quick cooking zone  $\varnothing$  14,5 cm (1100 W), converts to 14.5 x 24 cm (2000 W) roasting zone.  
1 Super-Quick cooking zone  $\varnothing$  14,5 cm (1000 W), converts to  $\varnothing$  21 cm (2200 W) cooking zone.  
1 Super-Quick cooking zone  $\varnothing$  18 cm (1800 W).  
1 Super-Quick cooking zone  $\varnothing$  14.5 cm (1200 W).

#### Handling

Continuously variable energy controls.

#### Features

Cooking zone marking.

#### Safety

Individual residual heat indicators.  
Operation indicator.

#### Planning notes

Immersion depth 58 mm.  
Under the appliance, a 60 mm clearance must be observed from side panels or intermediate shelf must be planned.  
Appliance can be snapped into the worktop from above.  
Securing rail on the rear and the front.  
Appliance weight: approx. 14 kg.

#### Connection

Total connected load 7.2 kW.  
Plan a connection cable.

#### Characteristics

**Product name/family**  
Cooking zone ceramic

**Construction type**  
Built-in

**Energy input**  
Electric

**Total number of positions that can be used at the same time**  
4

**Type of control setting devices**  
Required niche size for installation (HxWxD)  
58 x 680-680 x 490-490

**Width of the product (mm)**  
700

**Dimensions of the product (mm)**  
58 x 700 x 523

**Dimensions of the packed product (HxWxD) (mm)**  
193 x 810 x 600

**Net weight (kg)**  
13.741

**Gross weight (kg)**  
15.0

**Residual heat indicator**  
Separate

**Location of control panel**  
Hob front

**Type of external control possibility**  
Basic surface material  
Ceramic

**Color of surface**  
Black, Black

**Color of frame**  
Black

**Approval certificates**  
CE, Eurasian, Ukraine, VDE

**Length electrical supply cord (cm)**  
Knob Material  
Full metal

**Sealed Burners**  
No

**heating with booster**  
Type of pan support  
Natural Gas Connection Rating (BTU)  
LP Gas Connection Rating (BTU)  
Dimension of 1st heating element (in)  
Power of heating element (kW)  
1 ; 2.2

**Power of 1st burner (BTU)**  
Dimension of 2nd heating element (in)  
Power of 2nd heating element (kW)  
Power of 2nd burner (BTU)  
Dimension of 3rd heating element (in)  
Power of 3rd heating element (kW)  
1.2

**Power of 3rd burner (BTU)**  
Dimension of 4th heating element (in)  
Power of 4th heating element (kW)  
Power of 4th burner (BTU)  
Dimension of 5th heating element (in)  
Power of 5th heating element (kW)  
1.1 ; 2

**Power of 5th burner (BTU)**  
Dimension of 6th heating element (in)  
Power of heating element (kW in boost)  
Power of 2nd heating element (kW in boost)  
Power of 3rd heating element (kW in boost)  
Power of 4th heating element (kW in boost)  
Power of 5th heating element (kW in boost)  
Power of 6th heating element (kW in boost)

**Consumption and connection features**  
Electrical connection rating (W)  
7200

**Gas connection rating (W)**  
Current (A)  
3\*16

**Voltage (V)**  
230

**Frequency (Hz)**  
60; 50

**Universal Product Code**  
825225915881

#### Color Variants


**VE270114**  
**Stainless steel control panel**  
**Width 70 cm**

#### Included accessories

1 x glass scraper.

#### Installation Accessories

**VV200014**  
**Stainless steel connection strip for combination with other Vario appliances of the 200 series**



Mounting rail  
(rear and front)

