



Color Variants
VF230614
Stainless steel control panel
Width 28 cm

Included accessories
1 x stainless steel cover.
1 x deep-fat frying basket.

Optional accessories
VD201014
Brushed stainless steel appliance cover

Installation Accessories
VV200014
Stainless steel connection strip
for combination with other Vario
appliances of the 200 series

VF230614
Vario deep fryer 200 series
Stainless steel control panel
Width 28 cm

Can be combined with the cooktops
of the Vario 200 series to a harmonic
unity
Generous control panel for
comfortable and secure operation
Three-zone basin, without flavour
transfer
Exact temperature control, no drop in
output
Integrated frying basket suspension

Cooking zones
Three-zone basin.
Oil capacity 3.5 litres.

Handling
Function display.
Electronic temperature control from
135 °C to 190 °C, in 5 °C steps.

Features
Gentle fat melting setting.
Foaming zone.
Frying zone.
Cold oil zone.
Swing-out heating element (2300 W).
Electronic short-term timer up to 90
min.

Safety
Remaining time display.
Electronic overheating protection.
Child lock.
Safety shut-off.

Planning notes
Plan a door in the bottom cabinet for
operation of the oil drain valve.
VF 230 and VK 230 must not be
installed directly next to each other.
Appliance can be snapped into the
worktop from above.
Appliance weight: approx. 8 kg.

Connection
Total connected load 2.3 kW.
Connecting cable 1.7 m without plug.

Characteristics
Product name/family
Vario/Domino deep fryer
Built-in / Free-standing
Built-in
Energy input
Electric
Type of control
Electronic
Type of control setting and signalling
devices
Sword knobs
Required niche size for installation
(HxWxD)
420 x 268 x 490
Width of the product (mm)
288
Dimensions of the product (mm)
420 x 288 x 523
Dimensions of the packed product
(HxWxD) (mm)
415 x 403 x 600
Net weight (kg)
8.441
Gross weight (kg)
10.0
Power on indicator
No
Location of control panel
Type of regulation
Stepless energy regulated
Basic surface material
Stainless steel
Color of surface
Stainless steel, Stainless steel
Color of frame
Stainless steel
Approval certificates
CSA, ETL, UL
Length electrical supply cord (cm)
170

Consumption and connection features
Electrical connection rating (W)
2300
Current (A)
14
Voltage (V)
208/220-240
Frequency (Hz)
60
2019-10-29
Page 1

