

Color Variants VG295220CA Black control panel Width 90 cm

Included accessories

1 x WOK attachment ring.

Optional accessories WP400001 Wok pan made of multiple-layer material

VG295220CA Gas cooktop 200 series Black control panel Width 90 cm Natural gas 15 mbar Wok burner with up to 5.5 KW

Control panel for comfortable and secure operation Mechanical power level regulation for 9 power levels, with exact setting and reproduction of flame size Multi-ring burner of solid, heat-resistant brass as used in professional kitchen Solid smooth-surface cast iron pan supports Up to 17.5 kW on 5 burners

Cooking zones

1 multi-ring wok burner (300 W – 5500 W), suitable for pots up to max. ø 32 cm.

2 two-ring high output burners (170 W – 4000 W), suitable for pots up to max. σ 28 cm.

2 two-ring standard burners (170 W – 2000 W), suitable for pots up to max. ø 24 cm.

Handling

Control knobs with illuminated ring. Integrated control panel. One-handed operation. Electric ignition.

Features

Three-part cast iron pan support with flat, continuous pot surface. Brass burner rings.

Safety

Thermoelectric safety pilot. Residual heat indication. Operation indicator.

Planning notes

No intermediate shelf required. Appliance can be snapped into the worktop from above. Rear panel and wall trims must be heat-resistant and consist of a nonflammable material. Installation in a 90 cm wide lower cabinet is required. A minimum lateral clearance of at least 300 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted. With a total connected load of more than 11 kW local regulations concerning room ventilation, room size and combination of extraction or recirculation hoods must be observed. Minimum clearance between gas cooktop(s) with more than 11 kW and ventilation hood 70 cm. Appliance weight: approx. 29 kg.

Connection

Total connected load gas 17.5 KW. Total connected load electric 10 W. Connecting cable 1.5 m with plug.

Characteristics

Product name/family gas hob w integrated controls Built-in / Free-standing Built-in Energy input Gas Total number of positions that can be used at the same time

Required niche size for installation (HxWxD) 106 x 885 x 492

Width of the appliance

914 Dimensions 106 x 914 x 510 Dimensions of the packed product (HxWxD) (mm) 290 x 700 x 1010 Net weight (kg) 28.879 Gross weight (kg) 31.2 Residual heat indicator Location of control panel Basic surface material brushed stainless steel Color of surface Stainless steel Color of frame Stainless steel Approval certificates

CSA, CSA, CSA

Length electrical supply cord (cm) 150

Connection rating (W) 10

Gas connection rating (W) 17500

Current (A) 15

Voltage (V) 110-120

Frequency (Hz) 60

Consumption and connection features 2021-07-09

Page 1













