



Color Variants

VI230114
Stainless steel control panel
Width 28 cm

Installation Accessories

SH230001
Hinge holder for fitting the appliance cover
VV200014
Stainless steel connection strip for combination with other Vario appliances of the 200 series

VI230114

Vario induction cooktop 200 series
Stainless steel control panel
Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
Generous control panel for comfortable and secure operation

Cooking zones

1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling

Control knobs with cooking zone and output level markings.
Electronic power control in 9 output levels.

Features

Cooking zone marking.
Pot detection.
Booster function for both cooking zones.

Safety

Residual heat indication.
Operation indicator.
Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Immersion depth 50 mm. The wok pan WP 400 001 cannot be used with this appliance. Appliance must be fixed from underneath. Cooktop clamping range: 20 - 40 mm. Appliance weight: approx. 7 kg.

Connection

Total connected load 3.7 kW.
Connecting cable 1.5 m without plug.

Characteristics

Product name/family
Vario/Domino cooking zone cera

Built-in / Free-standing
CONSTR_TYPE.Built-in

Energy input
Electric

Total number of positions that can be used at the same time
2

Required niche size for installation (HxWxD)
50 x 268 x 490

Width of the product (mm)
288

Dimensions of the product (mm)
50 x 288 x 523

Dimensions of the packed product (HxWxD) (mm)
175 x 400 x 605

Net weight (kg)
6.581

Gross weight (kg)
8.0

Residual heat indicator
Separate

Location of control panel
Hob front

Basic surface material
Ceramic

Color of surface
Black, Stainless steel

Color of frame
Stainless steel

Approval certificates
AENOR, CE

Length electrical supply cord (cm)
150

Consumption and connection features

Electrical connection rating (W)
3700

Gas connection rating (W)

Current (A)

Voltage (V)
220-240

Frequency (Hz)
50; 60

2019-10-24
Page 1

