



**VI260114**  
**Vario induction cooktop 200 series**  
**Stainless steel control panel**  
**Width 60 cm**

Can be combined with the cooktops of the Vario 200 series to a harmonic unity  
 Generous control panel for comfortable and secure operation

**Cooking zones**

1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).  
 2 induction cooking zones ø 18 cm (1800 W, with booster 2500 W).  
 1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

**Handling**

Control knobs with cooking zone and output level markings.  
 Electronic control in 9 output levels.

**Features**

Cooking zone marking.  
 Pot detection.  
 Booster function for all cooking zones (two cooking zones - left and right - can be operated simultaneously with booster function).

**Safety**

Residual heat indication.  
 Operation indicator.  
 Safety shut-off.

**Planning notes**

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Immersion depth 49 mm. Cooktop clamping range: 20 - 40 mm. Intermediate shelf is recommended. Appliance must be fixed from underneath. Appliance weight: approx. 13 kg.

**Connection**

Total connected load 7.4 kW.  
 Connecting cable 1.5 m without plug.

**Characteristics**

**Product name/family**  
 Cooking zone ceramic

**Construction type**  
 Built-in

**Energy input**  
 Electric

**Total number of positions that can be used at the same time**  
 4

**Type of control setting devices**  
 Required niche size for installation (HxWxD)  
 49 x 560-560 x 490-490

**Width of the product (mm)**  
 580

**Dimensions of the product (mm)**  
 49 x 580 x 523

**Dimensions of the packed product (HxWxD) (mm)**  
 113 x 1091 x 709

**Net weight (kg)**  
 12.970

**Gross weight (kg)**  
 14.0

**Residual heat indicator**  
 Separate

**Location of control panel**  
 Hob front

**Type of external control possibility**  
 Basic surface material  
 Ceramic

**Color of surface**  
 Black, Stainless steel

**Color of frame**  
 Stainless steel

**Approval certificates**  
 AENOR, CE

**Length electrical supply cord (cm)**  
 150

**Knob Material**  
 Full metal

**Sealed Burners**  
 No

**heating with booster**  
 All

**Type of pan support**  
 Natural Gas Connection Rating (BTU)  
 LP Gas Connection Rating (BTU)

**Dimension of 1st heating element (in)**  
**Power of heating element (kW)**  
 1.8

**Power of 1st burner (BTU)**  
**Dimension of 2nd heating element (in)**  
**Power of 2nd heating element (kW)**  
**Power of 2nd burner (BTU)**  
**Dimension of 3rd heating element (in)**  
**Power of 3rd heating element (kW)**  
 1.8

**Power of 3rd burner (BTU)**  
**Dimension of 4th heating element (in)**  
**Power of 4th heating element (kW)**  
**Power of 4th burner (BTU)**  
**Dimension of 5th heating element (in)**  
**Power of 5th heating element (kW)**  
 1.4

**Power of 5th burner (BTU)**  
**Dimension of 6th heating element (in)**  
**Power of heating element (kW in boost)**  
 [2.5]

**Power of 2nd heating element (kW in boost)**  
**Power of 3rd heating element (kW in boost)**  
 [2.5]

**Power of 4th heating element (kW in boost)**  
**Power of 5th heating element (kW in boost)**  
 [1.8]

**Power of 6th heating element (kW in boost)**

**Consumption and connection features**  
**Electrical connection rating (W)**  
 7400

**Gas connection rating (W)**  
**Current (A)**  
**Voltage (V)**  
 220-240

**Color Variants**

**VI260114**  
**Stainless steel control panel**  
**Width 60 cm**

**Installation Accessories**

**VV200014**  
**Stainless steel connection strip for combination with other Vario appliances of the 200 series**

