



VI270114
Vario induction cooktop 200 series
Stainless steel control panel
Width 70 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
 Generous control panel for comfortable and secure operation

Cooking zones

1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
 2 induction cooking zones ø 18 cm (1800 W, with booster 2500 W).
 1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling

Control knobs with cooking zone and output level markings.
 Electronic control in 9 output levels.

Features

Cooking zone marking.
 Pot detection.
 Booster function for all cooking zones (two cooking zones - left and right - can be operated simultaneously with booster function).

Safety

Residual heat indication.
 Operation indicator.
 Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Immersion depth 49 mm. Cooktop clamping range: 20 - 40 mm. Intermediate shelf is recommended. Appliance must be fixed from underneath. Appliance weight: approx. 14 kg.

Connection

Total connected load 7.4 kW.
 Connecting cable 1.5 m without plug.

Characteristics

Product name/family
 Cooking zone ceramic

Construction type
 Built-in

Energy input
 Electric

Total number of positions that can be used at the same time
 4

Type of control setting devices
 Required niche size for installation (HxWxD)
 49 x 680-680 x 490-490

Width of the product (mm)
 700

Dimensions of the product (mm)
 49 x 700 x 523

Dimensions of the packed product (HxWxD) (mm)
 117 x 938 x 625

Net weight (kg)
 14.327

Gross weight (kg)
 16.0

Residual heat indicator
 Separate

Location of control panel
 Hob front

Type of external control possibility
 Basic surface material
 Ceramic

Color of surface
 Black, Stainless steel

Color of frame
 Stainless steel

Approval certificates
 AENOR, CE

Length electrical supply cord (cm)
 150

Knob Material
 Full metal

Sealed Burners
 No

heating with booster
 All

Type of pan support
 Natural Gas Connection Rating (BTU)
 LP Gas Connection Rating (BTU)
 Dimension of 1st heating element (in)
 Power of heating element (kW)
 1.8

Power of 1st burner (BTU)
 Dimension of 2nd heating element (in)
 Power of 2nd heating element (kW)
 Power of 2nd burner (BTU)
 Dimension of 3rd heating element (in)
 Power of 3rd heating element (kW)
 1.8

Power of 3rd burner (BTU)
 Dimension of 4th heating element (in)
 Power of 4th heating element (kW)
 Power of 4th burner (BTU)
 Dimension of 5th heating element (in)
 Power of 5th heating element (kW)
 1.4

Power of 5th burner (BTU)
 Dimension of 6th heating element (in)
 Power of heating element (kW in boost)
 [2.5]

Power of 2nd heating element (kW in boost)
 Power of 3rd heating element (kW in boost)
 [2.5]

Power of 4th heating element (kW in boost)
 Power of 5th heating element (kW in boost)
 [1.8]

Power of 6th heating element (kW in boost)

Consumption and connection features
 Electrical connection rating (W)
 7400

Gas connection rating (W)

Current (A)
Voltage (V)
 220-240

Color Variants

VI270114
Stainless steel control panel
Width 70 cm

Installation Accessories

VV200014
Stainless steel connection strip for combination with other Vario appliances of the 200 series

