



VK230114
Vario steamer 200 series
Stainless steel control panel
Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
 Generous control panel for comfortable and secure operation
 Steaming in cooktop size
 Exact water temperature control from 45 °C to 95 °C
 Cooking on two levels, without flavour transfer

Cooking zones
 Water capacity 1 to 6 litres.

Handling
 Function display.
 Electronic water temperature control from 45 °C to 95 °C, in 5 °C steps.
 Steam cooking level with electronic steam control for pressureless cooking.

Features
 Automatic boiling point detection.
 Motor-driven water drain valve 1/2".
 Electronic short-term timer up to 90 min.
 Special heating system.

Safety
 Remaining time display.
 Child lock.
 Operation indicator.
 Automatic shut off.

Planning notes
 Access to drain in bottom cabinet is required.
 Appliance is intended for fixed water outlet connection, but can be fitted without fixed connection by using the special accessory AG 060.
 Seal the worktop cutout.
 Appliance can be snapped into the worktop from above.
 A minimum clearance of at least 200 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted.
 In case of suspended cabinets a ventilation hood must be installed above the steamer.
 If a cover is fitted, the glass lid must be removed when closing it.
 VK 230 and VF 230 must not be installed directly next to each other.
 In combination with the downdraft ventilation VL 040/041, this must be planned on the right of VK.
 Appliance weight: approx. 11 kg.

Connection
 Total connected load 2.3 kW.
 Connecting cable 1.7 m without plug.

Characteristics
Product name/family
 Vario/Domino steam cooker
Built-in / Free-standing
 Built-in
Energy input
 Electric
Type of control
 Electronic
Type of control setting and signalling devices
 Sword knobs
Required niche size for installation (HxWxD)
 280 x 268 x 490
Width of the product (mm)
 288
Dimensions of the product (mm)
 280 x 288 x 523
Dimensions of the packed product (HxWxD) (mm)
 385 x 420 x 610
Net weight (kg)
 11.137
Gross weight (kg)
 12.7
Power on indicator
 Yes
Location of control panel
Type of regulation
 Stepless energy regulated
Basic surface material
 Stainless steel
Color of surface
 Stainless steel
Color of frame
Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)
 170


Consumption and connection features
Electrical connection rating (W)
 2300
Current (A)
 16; 10
Voltage (V)
 230-240
Frequency (Hz)
 60; 50
 2019-11-25
 Page 1

Color Variants
VK230114
Stainless steel control panel
Width 28 cm


Included accessories
 2 x cooking insert.
 1 x glass cover.
 1 x hand grip.
 1 x residuary filter.
 1 x water drain valve.

Optional accessories
FK023000
Pasta basket
GE020010
Unperforated cooking insert
GE020020
Perforated cooking insert
VD201014
Brushed stainless steel appliance cover


Installation Accessories
VV200014
Stainless steel connection strip for combination with other Vario appliances of the 200 series




Mounting rail
 (rear and front)



Εάν η απόσταση μεταξύ των τοίχων του γκαζιού είναι μικρότερη από 300 mm, τότε ο φούρνος πρέπει να εγκατασταθεί με την πλάτη στον τοίχο. Η απόσταση μεταξύ των τοίχων του γκαζιού πρέπει να είναι τουλάχιστον 300 mm. Σε περίπτωση αμφιβολίας, συμβουλευθείτε τον κατασκευαστή.



Εάν η απόσταση μεταξύ των τοίχων του γκαζιού είναι μικρότερη από 120 cm, τότε ο φούρνος πρέπει να εγκατασταθεί με την πλάτη στον τοίχο. Η απόσταση μεταξύ των τοίχων του γκαζιού πρέπει να είναι τουλάχιστον 120 cm. Σε περίπτωση αμφιβολίας, συμβουλευθείτε τον κατασκευαστή.



Εάν η απόσταση μεταξύ των τοίχων του γκαζιού είναι μικρότερη από 105 cm, τότε ο φούρνος πρέπει να εγκατασταθεί με την πλάτη στον τοίχο. Η απόσταση μεταξύ των τοίχων του γκαζιού πρέπει να είναι τουλάχιστον 105 cm. Σε περίπτωση αμφιβολίας, συμβουλευθείτε τον κατασκευαστή.

