



#### Color Variants

VL040715

Stainless steel control panel

Width 8.5 cm

#### Optional accessories

AD724042

Connection piece for round pipe DN 150

AS070001

Connecting piece for extension in the case of installation next to VK or VF

LS041001

Ventilation moulding for VL 200 next to gas appliance

VV200014

Stainless steel connection strip for combination with other Vario appliances of the 200 series

#### Required installation accessories

AD724041

Round duct connection additional adapter for VL 414 on the side

Metal zinc coated

#### Installation Accessories

AS070001

Connecting piece for extension in the case of installation next to VK or VF

Metal zinc plated

LS041001

Ventilation moulding for VL 200 next to gas appliance

Stainless steel

VV200014

Stainless steel connection strip for combination with other Vario appliances of the 200 series

VL040715

Vario downdraft ventilation 200 series

Stainless steel control panel

Width 8.5 cm

Expansion element

Air extraction with remote fan unit AR 400 741

Ventilation element integrated in the worktop, extendable  
Highly efficient ventilation system at the cooktop  
Minimal planning and easy installation for air recirculation

#### Output

Maximum air output in combination with remote fan units s. table remote fan units on page xxx.  
Sound power level depends on the built-in situation.

#### Features

Ventilation grille, washable.  
Metal grease filter with grease drip tray, dishwasher-safe.  
No duct connecting piece included.

#### Planning notes

Only in combination with VL 041 115.  
Please refer to page xxx for recommended configurations of downdraft ventilations and remote fan units and the needed ducting elements.  
Maximum cooktop width between 2 VL: 60 cm (exception: VI/VE 270).  
If installed next to gas appliances, the ventilation moulding LS 041 001 is recommended to ensure maximum performance of the cooktop. If installed next to gas appliances, flat ducts must not be used for the piping up to the fan unit.  
When having installed the ventilation moulding LS 041 001 the wok pan WP 400 001 can not be used.  
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.  
Do not fit in drawer area.  
Please ensure when installing the exhaust air ducting that no sharp bends are caused and that the cross-section of the ducting is not constricted in any way.  
For downdraft configurations with maximum lengths of exhaust air ducts go to Rodun at [www.gaggenau.com](http://www.gaggenau.com).  
Appliance weight: approx. 1 kg.  
Please read additional planning notes on page xx.

#### Connection

Connecting cable 2.0 m with plug.

#### Characteristics

Product name/family

Color chimney

Typology

Approval certificates

CSA, ETL, UL

Length electrical supply cord (cm)  
200

Required niche size for installation (HxWxD)  
320mm x 78mm x 490mm

Height of the chimney (mm)

Height of product, without chimney (mm)

Net weight (kg)  
1.335

Type of control

Number of speed settings

Maximum output air extraction (m3/h)

Boost position output recirculating (m3/h)

Maximum output recirculating air (m3/h)

Boost position air extraction (m³/h)

Number of lights

Noise level (dB)

Diameter of air outlet (mm)  
150

Grease filter material  
Washable aluminium

Odour filter  
No

Operating Mode  
Convertible

Delay Shut off modes

Required accessories

Optional accessories  
AD724042, AS070001, LS041001, VV200014

Type of lamps used

Total power of the lamps (W)

Grease filter type  
Multilayer

Clean filter reminders

#### Consumption and connection features

Connection Rating (W)

Current (A)  
10

Voltage (V)  
120

Frequency (Hz)  
60

Plug type

Installation typology  
Built-in

Universal Product Code  
825225912248

Material body  
Stainless steel

Approval certificates  
CSA, ETL, UL

Length of electrical supply cord (in)  
Plug type

Dimensions of the product, with chimney (if exists) (in)  
7 1/16" / 7 1/16" x 3 3/8" x

Dimensions of the packed product (in)  
7.28 x 23.03 x 11.61

Height of the chimney (in)  
Vertical rise height

Required distance above cooktop/ranges

Net weight (lbs)  
3

Gross weight (lbs)  
9

Motor location  
N/A

Maximum output recirculating air (CFM)

Diameter of air duct (in) top

Diameter of air duct (in) back

Discharge direction

No-return airflow flap  
No

Length electrical supply cord (cm)  
200

Dimensions of the product, with chimney (if exists) (mm)  
180 x 85 x 523

VL 040/041 with AD 724 042/041

