



WS463710

warming drawer 400 series
stainless steel-backed glass front
WS463710

For side-by-side combination of 76 cm BO and
60 cm BS/BM/CM

Handleless drawer.

Bright interior light

Cushioned closing system.

Hygienic stainless steel interior with glass
bottom.

4 power levels in the temperature range 40 °C
to 80 °C (glass surface)

Also for preparing and cooking meals, and for
keeping meals warm

Heating methods

Defrosting of meals/proving of yeast dough.

Preheating of small beverage containers/cups.

Keeping meals warm/slow cooking meals.

Warming cookware/plates.

Handling

Rotary knob operation.

Recessed grip at the front bottom of the drawer.

Features

Net volume 1 cu. ft.

Volume capacity: Dinner service for 8 people
including ø 9 1/2 " (24 cm) plates and soup
bowls, additional bowls and a serving dish
depending on size.

Max. load 25 kg.

Usable interior dimensions

W 18 11/16 " x H 5 3/16 " x D 18 1/16 ".

Heating under glass bottom for easy cleaning.

Fan for even heat distribution for fast warming
ovenware.

Status indicator, visible in the glass front.

Glass bottom made of safety glass.

Planning notes

The panel surface of the appliance extends 1
7/8 " (47 mm) from the furniture cavity.

Installation of BO/BS above WS with
dimensionally stable intermediate shelf.

Installation of BS/BM/CM above WS in 23 3/16
" (66,5 cm) niche with intermediate floor (gap of
7 mm between WS and BS).

The socket can be planned behind the
appliance.

Connection

Total connected load 0.81 KW.

Total Amps: 10 A.

120 V / 60 Hz.

Connection cable 71 ", with plug.

